



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,25
breadth (mm)	1480
depth (mm)	900
height (mm)	1260

PROFESSIONAL DESCRIPTION

REFRIGERATED WOODEN DISPLAY TROLLEY complete with DOME and SUPPORT SHELVES, temperature -5°/+5°C:

- **WALNUT or WENGE'** colored **solid wood structure** ;
- **semicircular dome** in **plexiglass**;
- **capacity 4 Gastro-Norm 1/1 trays, h 150 mm** (not included);
- **temperature -5°/+5°C** with **lids in place**;
- **static refrigeration**;- R134A refrigerant gas ;
- **2 support shelves, one folding on the front and one fixed at the top**;
- 4 multi-directional wheels .

Operating environmental conditions :

- Ambient Temperature Max 26°C
- Relative Humidity 60 %

CE mark

AVAILABLE MODELS

FO-ELR2826BTW

Refrigerated display trolleys

€ 1.889,02

VAT excluded
Shipping to be calculated



Delivery from 4 to 9 days

FO-ELR2826BT

Refrigerated display trolleys

€ 1.889,02

VAT excluded

Shipping to be calculated

Delivery from 4 to 9 days

