



#### PROFESSIONAL DESCRIPTION

**CENTRIFUGAL FANS with DIRECT COUPLING, DOUBLE INTAKE for SUCTION BOXES, COMPLETE RANGE with flow rate from 1500 to 10,000 metres/cubic meters/hour :**

- **double inlet centrifugal fans with motor directly coupled to the impeller** (forward blades);
- **single-phase motor with permanent capacitor inserted , 4 or 6 poles , or three-phase ;**
- screw fan in **galvanized sheet metal ;**
- working ambient temperature from -20°C to +40°C;
- engine normally mounted on self-aligning bushings with lubricant reserve;
- class B insulation.

**CE mark**  
**Made in Italy**

#### AVAILABLE MODELS

##### AIF-DSDM10/8-4



**Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 4 poles, 1260 RPM, max flow rate 2800 m3/h, V.230/1, Kw.0.55, dim.mm.429x265x444h**

**€ 278,04**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

##### AIF-DSDM9/9-4



**Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 4 poles, 1300 RPM, max flow rate 2500 m3/h, V.230/1, Kw.0.42, dim.mm.378x298x390h**

**€ 283,47**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

##### AIF-DSDM9/7-4

**Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 4 poles, 1400 RPM, max flow rate 1800 m3/h, V.230/1, Kw.0.42, dim.mm.378x232x390h**

**€ 295,54**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days



**AIF-DSDM9/7-6**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 970 RPM, max flow rate 1500 m<sup>3</sup>/h, V.230/1, Kw.0.25, dim.mm.378x232x390h

**€ 297,26**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM9/9-6**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 940 RPM, max flow rate 2200 m<sup>3</sup>/h, V.230/1, Kw.0.25, dim.mm.378x298x390h

**€ 302,43**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM10/10-4**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 4 poles, 1200 RPM, max flow rate 2900 m<sup>3</sup>/h, V.230/1, Kw.0.55, dim.mm.429x331x444h

**€ 316,47**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM10/8-6**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 880 RPM, max flow rate 2300 m<sup>3</sup>/h, V.230/1, Kw.0.25, dim.mm.429x265x444h

**€ 342,82**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM12/12-6/A-M**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 940 RPM, max flow rate 4000 m<sup>3</sup>/h, V.230/1, Kw.0.57, dim.mm.497x395x522h

**€ 433,21**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM12/12-6/B-M**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 940 RPM, max flow rate 4600 m<sup>3</sup>/h, V.230/1, Kw.0.736, dim.mm.497x395x522h

**€ 453,89**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM12/12-6-T**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 890 RPM, max flow rate 6000 m<sup>3</sup>/h, V.400/3, Kw.1.1, dim.mm.497x395x522h

**€ 496,99**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

**AIF-DSDM15/15-6-T**



Double inlet centrifugal fan with motor directly coupled to the forward-bladed impeller, for installation in an extractor box, 1 SPEED, 6 poles, 920 RPM, max flow rate 10000 m<sup>3</sup>/h, V.400/3, Kw.2.2, dim.mm.579x474x616h

**€ 718,65**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 8 to 15 days

