



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



#### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,275
<b>net weight (Kg)</b>	108
<b>gross weight (Kg)</b>	128
<b>breadth (mm)</b>	1795
<b>depth (mm)</b>	700
<b>height (mm)</b>	850

#### PROFESSIONAL DESCRIPTION

**REFRIGERATED TABLE 3 DOORS, with MONOBLOC, PLUG-IN SYSTEM, capacity 417 litres, temperature -2°C /+8°C, Gastronorm 1/1, ECOLOGICAL in Class D:**

- **AISI 201 stainless steel structure,**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **circular flow of the cold air so as not to directly touch the product ;**
- **electronic temperature control with digital thermostat ;**
- operating temperature -2°/+8°C;
- electric resistance around the door frame to eliminate condensation;
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**

- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- possibility of leaning against the wall;
- **easy interchangeability of doors with two and three drawer chests ;**
- **ECOLOGICAL refrigeration unit with R600a gas ;**
- **Energy Class D ;**
- insulation thickness 60 mm;
- max ambient temperature/humidity: +35 °C / 55%HR;
- internal dimensions (mm): 1335x530x560;
- external dimensions (mm): 1795x700x850h.

**Supplied :**

- n.3 GN 1/1 grids (mm 530x325)
- n.6 guides.




**Options/Accessories :**

- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes
- Set of 2 drawers
- Set of 3 drawers

**NOTE: IT IS RECOMMENDED TO INSTALL ONLY THE CHEST OF DRAWERS WITH 2 DRAWERS IN THE COMPARTMENT NEAR THE REFRIGERATING UNIT , so as not to obstruct the circulation of the cold.**

**CE mark**  
**Made in ASIA**

CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-G-GN3100TN-FC</b>	3-door refrigerated table, with monobloc, plug-in system, capacity 417 litres, temperature -2°/+8°C, ventilated refrigeration, Gastronorm 1/1, ECOLOGICAL in Class C, Gas R600a, V.230/1, Kw.0,275, Weight 108 Kg, dim.mm.1795x700x850h	<b>€ 1.046,11</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 8 to 15 days

TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>FOGRP11</b> 	<b>GN 1/1 plasticized grid</b>	<b>€ 8,67</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days
<b>FOCG11</b> 	<b>Pair of guides for GN 1/1 grid support</b>	<b>€ 11,56</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days
<b>FO-RUO120</b> 	<b>Forcar - 4 Wheel Kit, 2 with Brake</b>	<b>€ 78,63</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days
<b>FO-C12-FC</b>	<b>TECHNOCHEF - 2-drawer set, Mod.C12-FC</b>	<b>€ 275,29</b> <i>VAT excluded</i> <b>Shipping to be calculated</b>



Delivery from 4 to 9 days

FO-C13-FC

TECHNOCHEF - 3-drawer set, Mod.C13-FC

€ 385,41

VAT excluded

Shipping to be calculated

Delivery from 4 to 9 days

