

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD	
power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,7
net weight (Kg)	127
breadth (mm)	1870
depth (mm)	715
height (mm)	950

PROFESSIONAL DESCRIPTION

$\textbf{FREEZING/FREEZER\ TABLE\ 3\ DOORS\ with\ BACKPACK,\ capacity\ 460\ litres,\ operating\ temperature\ \textbf{-18}^\circ\text{/-}22^\circ\text{C}:}$

- internal and external structure in Stainless Steel , with the exception of the external bottom in Galvanized Steel;
- rounded internal corners;
- compartments suitable for inserting Gastro-Norm 1/1 grills or trays (530x325 mm);
- capacity 460 litres;
- $\circ~$ operating temperature -18°/-22°C;
- $\circ \ \ \textbf{insulation in CFC-free polyurethane} \ , \ \text{injected at high pressure}; \\$
- insulation thickness of BT tables: 60 mm;
- $\circ\,$ doors with automatic closing and magnetic seal;
- **electronic control instrument with 2 NTC probes** , evaporator resistance, discharge resistance, door edge resistance, thermostatic valve;
- ventilated refrigeration;
- removable and tropicalized monobloc refrigeration unit as standard (ambient temperature +43°C and relative humidity of 65%);
- o works with R404A/R507 gas;
- $\circ\,$ fully automatic defrosting and evaporation of condensation water;
- equipped with an insulating undertop;
- $\circ \ \, \textbf{Stainless Steel feet adjustable in height (110/190 \ \text{H mm});} \\$
- o dim.mm.1870x715x950/1020.

Supplied:

o 1 Rilsan GN 1/1 grill and 2 L-shaped stainless steel guides per door

CE mark Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
TD-TF03MIDBTAL	FREEZING/FREEZER TABLE 3 DOORS with BACKPACK, TECNODOM brand, capacity 460 litres, operating temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0, 7, weight 127 kg, dim.mm.1870x715x950h	