



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,385
net weight (Kg)	110
breadth (mm)	710
depth (mm)	800
height (mm)	2030

PROFESSIONAL DESCRIPTION

1 DOOR REFRIGERATOR CABINET, capacity 700 litres, operating temperature -2°/+10°C :

- **internal and external structure in stainless steel** except for the external bottom, ceiling and back in galvanized steel;
- rounded internal corners;
- **suitable for containing Gastro-Norm 2/1 grids or trays** (650x530 mm);
- capacity 700 lt;
- operating temperature -2°/+10°C;
- CFC-free polyurethane insulation, injected at high pressure;
- **insulation thickness : 60 mm ;**
- self-closing doors with magnetic seal;
- **ventilation stop device when door is opened ;**
- **front electronic control panel** with 2 NTC probes;
- evaporator resistance;
- **ventilated refrigeration ;**
- extractable and tropicalized monoblock refrigeration unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R290 gas;
- **fully automatic defrosting and evaporation of condensation water ;**
- reversible door;
- **height-adjustable stainless steel feet** (110/190 H mm);
- dim.mm.710x800x2030/2100h.

Included :

- 3 Rilsan plasticized grids GN 2/1
- 6 stainless steel guides
- fan stop

CE mark**Made in ITALY**

CODE	DESCRIPTION	PRICE/DELIVERY
TD-AF07MIDMTN	1 door REFRIGERATOR CABINET, Brand TECNODOM, capacity 700 lt, operating temperature -2°/+10°C, ventilated refrigeration, Gastro-Norm 2/1, V.230/1, Kw.0,385, Weight 110 Kg, dim.mm.710x800x2030h	€ 1.130,49 <i>VAT excluded</i> Shipping to be calculated Delivery from 25 to 35 days

