



#### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,32
<b>net weight (Kg)</b>	95
<b>breadth (mm)</b>	1000
<b>depth (mm)</b>	438
<b>height (mm)</b>	934

#### PROFESSIONAL DESCRIPTION

##### REFRIGERATED EXHIBITOR SHOW by BANCO with 3 PLANS, VENTILATED, temperature + 4 ° / + 10 ° C:

- **frame entirely in extruded anodized aluminum** with **mirror finish** and smooth **stainless steel external panels** ;
- **ventilation grilles** integrated with punched processing;
- **sliding doors** with anodized aluminum frame and steel handles;
- **200 lt capacity** ;
- **temperature + 4 ° / + 10 ° C** ;
- **ventilated refrigeration**;
- type of defrost: automatic at pause;
- refrigerant gas: R404a
- **LED lighting** with high luminous efficiency and energy saving;
- **electronic control unit with display and control panel** ;
- platinum color;
- polyamide feet.

##### Environmental operating conditions:

- Ambient temperature Max 26 ° C.
- Relative humidity 60%

##### Supplied :

- 2 grids of 899x292 mm

CE marking

CODE	DESCRIPTION	PRICE/DELIVERY
TCF318-001100	REFRIGERATED EXHIBITOR SHOW by BANCO with 3 PLANS, temperature + 4 ° / + 10 ° C, capacity lt.200, LED lighting, ventilated refrigeration, V.230 / 1, Kw.0.32, Weight 95 Kg, dim.mm .1000x438x934h	<b>€ 2.481,21</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 8 to 15 days

