

TECNOSERVICE'21 srl by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973

TECHNIC	AL CARD
power supply	Monofase
	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,54
net weight (Kg)	170
breadth (mm)	720
depth (mm)	620
height (mm)	1860
PROFESSIONA	DESCRIPTION

REFRIGERATED PASTRY SHOWCASE 1 DOOR, CURVE Line, with 4 DISPLAY SIDES, 5 ROTATING GLASS SHELVES, capacity 427 litres, temperature +4°/+10°C :

- external structure in silver anodized aluminium ;
- showcase built using insulating double glazing , compliant with EN UNI 1279;
- exposure on 4 sides ;
- 5 rotating glass shelves Ø 452 ;
- capacity 427 litres ;
- operating temperature +4°/+10°C ;
- " sensitive touch " control panel with a unique and exclusive design, the result of a long IT and design study;
- ventilated refrigeration ;
- automatic defrost ;
- · LED lighting as standard on both sides of the internal compartment;
- lumen/meter: 2 x 1200 lm;
- humidity: 75%;
- compressors and the touch screen thermostat are of the latest generation, guaranteeing high efficiency and low absorption, with notable advantages for operating economy;
- accuracy, solidity and technology are the prerogatives on which the CURVE line is based, an expression of solidity combined with
  practicality, capable of satisfying all types of use, where robustness and reliability come together in the name of tradition.

Accessories/Options :

locking with key

- glass shelf
- $\circ~$  support kit for glass and grilles
- suction cup kit
- adjustable feet kit
- mirror glass
- additional LED
- wooden crate packaging
- $\circ\;$  finishes and colours: RAL of your choice

## CE mark

## Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
SL-CPS450R	Refrigerated pastry display case with 1 door, CURVE line, with 4 display sides, 6 rotating glass shelves, capacity 427 litres, operating temperature +4°/+10°C, ventilated refrigeration, V.230/1, Kw. 0.54, weight 170 kg, dim.mm.720x620x1860h	
	TECHNICAL CARD	
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
SL-KV	Suction Cups Kit	
SL-KSVG	Support kit for glass and grids	
SL-KP25/80	Adjustable Feet Kit	
SL-RPV45/90/130	Glass shelf	
SL-LED	Additional Led	
SL-CC25/80	Key closure	
SL-VSP35/45	Mirror glass	
SL-IMLEG45/60	Wooden case packing	
SL-RAL	Finish and Colors	
PBLI - NAMP Bill - NAMP Bill - NAMP Bill - Namp Bill - Namp		

