



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



#### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,01
<b>Thermal input (Kw)</b>	17,5
<b>net weight (Kg)</b>	59
<b>breadth (mm)</b>	400
<b>depth (mm)</b>	900
<b>height (mm)</b>	900

#### PROFESSIONAL DESCRIPTION

##### **GAS FRYER on CABINET, MAXIMA 900 Line, TURBO Series, 1 20 lt TANK, BFLEX ELECTRONIC CONTROLS:**


- **worktop and front and side panels in AISI 304 stainless steel ;**
- **stainless steel burners** with oval honeycomb section;
- large surface oval section heat exchangers, placed directly inside the tank, for rapid and uniform heating;
- **pilot flame** and **thermocouple safety valve ;**
- AISI 304 stainless steel tank with wide rounded edges and large cold zone, below the burners, for the decanting of residues;
- the top, with rounded edges, incorporates a slightly inclined surface for supporting the baskets which facilitates the oil draining ;
- **temperature control via electronic control unit** with the following functions:
  - **temperature control from 100 to 190 °C ,**
  - **display of the set and working temperatures ,**
  - **" melting " and 100°C holding program** for the use of solid frying fats,
  - **self-diagnosis for any anomalies ;**
- manual reset **safety thermostat ;**
- ball drain tap, located inside the compartment, controlled by a handle with a heat-resistant grip;
- **24 month warranty .**

**Included:**  
◦ single basket

**CE mark**  
**Made in ITALY**

CODE	DESCRIPTION	PRICE/DELIVERY
BS-9GL20M-BF	GAS FRYER on CABINET, BERTO'S, MAXIMA 900 Line, TURBO Series, 1 TANK of 20 lt, Bflex Electronic Controls, thermal power Kw.17.5, Weight 59 Kg, dim.mm.400x900x900h	<b>€ 2.031,22</b> <i>VAT excluded</i> <b>Shipping to be calculated</b>  <b>Delivery</b> from 8 to 15 days



	L	20
	mm	302 x 402 x 340 h
	mm	255 x 335 x 125 h
	kW	17,5
	kcal/h	15.050
	TOT Btu/h	59.710
	G30/G31 kg/h	1,38
	G20 m³/h	1,85
	G25 m³/h	2,16
	kg	59



