



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Trifase
Volts	V 400/3 +N
frequency (Hz)	50
motor power capacity (Kw)	22,00
net weight (Kg)	55
breadth (mm)	400
depth (mm)	900
height (mm)	900

PROFESSIONAL DESCRIPTION

ELECTRIC FRYER on MOBILE, MAXIMA 900 Line, TURBO Series, 1 22 lt TANK , ANALOGUE CONTROLS, ENHANCED version:

- **worktop and front and side panels in AISI 304 stainless steel ;**
- **Incoloy stainless steel heating elements** positioned directly inside the tank, which can be folded into a vertical position to facilitate cleaning operations;
- **safety device** for turning off the electricity supply with resistors in a vertical position;
- **temperature control via thermostat from 80 to 190 °C** with more accurate detection thanks to the sensors placed inside the tank;
- **line indicator and temperature indicator ;**
- **AISI 304 stainless steel tank** with large rounded edges and large cold area, below the heating elements, for settling residues;
- the top, with rounded edges, incorporates a slightly inclined surface for placing the baskets which facilitates the draining of the oil;
- **ball drain cock** , located inside the compartment, controlled by a handle with athermal grip, with steel collection tray;
- **24 month warranty .**

Supplied:

- single basket

CE mark

Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
BS-E9F22-4MS	ELECTRIC FRYER on MOBILE, BERTO'S, MAXIMA 900	

line, TURBO Series, 1 TANK of 22 litres, Analogue controls, Enhanced version, V.400/3+N, Kw.22.00, Weight 55 Kg, dim.mm.400x900x900h







€ 1.980,46

VAT excluded

Shipping to be calculated

Delivery from 15 to 25 days



	L	22
	mm	306 x 460 x 295 h
	mm	260 x 400 x 150 h
	TOT kW	18 (E9F22-4M)
	kW	22 (E9F22-4MS)
	VOLT	380-415 V3N~ 50/60 Hz
	Kg	55

