



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Trifase
Volts	V 400/3 +N
frequency (Hz)	50
net weight (Kg)	100
breadth (mm)	800
depth (mm)	700
height (mm)	900

PROFESSIONAL DESCRIPTION

ELECTRIC COOKER WITH 4 ROUND PLATES on ELECTRIC OVEN GN 2/1 (mm 530x650), MACROS 700 line, HIGH POWER series :

- **worktop and front panels in AISI 304 stainless steel ;**
- **one-piece watertight** molded top;
- **cast iron plates with safety thermostat and 6-position selector** which activates **6 different concentric power zones ;**
- **4 round plates with a diameter of 220 mm each ;**
- **cooking zone power n°x Kw : 4 x 2.6 ;**
- voltage and work control lights;
- **Static electric oven** entirely made of **stainless steel** , with **4-level supports for GN 2/1 grids/trays** (mm530x650) ;
- **Grill with salamander function** in the upper part and **thermostat** that allows accurate **temperature regulation from 50 to 270 °C ;**
- **line light and temperature reaching light ;**
- **oven power kW 7.5 ;**
- **line indicator and temperature indicator ;**
- door and inner door pressed in AISI 304 stainless steel;
- high-resistance door handle in 20/10 thick AISI 304 steel;
- adjustable feet;
- **2 year warranty .**

Supplied :

- 1 anti-tipping oven rack

CE mark

CODE	DESCRIPTION	PRICE/DELIVERY
BS-E7P4+FE	ELECTRIC COOKER 4 PLATES on ELECTRIC OVEN GN 2/1, BERTOS, MACROS 700 line, HIGH POWER Series, with 4 ROUND plates Ø 220 mm, INDEPENDENT CONTROLS, 6 power levels, V.400/3+N, Kw.17, 9, weight 100 kg, dim.mm.800x700x900h	





macros 700



HIGH POWER

2,6 kW

2,6 kW

2,6 kW

2,6 kW

► Ø 220 mm

FE



7,5 kW

GN 2/1
530 x 650 mm x 4 pos.





macros 700



n. 4


Ø mm 220

kW 2,6

GN 2/1

mm 530 x 650 x 4 pos.


MULTIFUNCTION kW 7,5 (4,5 + 3)



380 - 415 V3N~



TOT. kW 17,9



900
35 3/8"

700
27 1/2"

800
31 1/2"

