



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



#### TECHNICAL CARD

<b>power supply</b>	Trifase
<b>Volts</b>	V 400/3 +N
<b>frequency (Hz)</b>	50
<b>net weight (Kg)</b>	129
<b>breadth (mm)</b>	1200
<b>depth (mm)</b>	700
<b>height (mm)</b>	900

#### PROFESSIONAL DESCRIPTION

**ELECTRIC COOKER 6 ROUND PLATES on ELECTRIC OVEN GN 2/1 (mm 530x650), MACROS 700 line, HIGH POWER series :**

- **worktop and front panels in AISI 304 stainless steel ;**
- **one-piece watertight** molded top;
- **cast iron plates with safety thermostat and 6-position selector** which activates **6 different concentric power zones ;**
- **6 round plates with a diameter of 220 mm each ;**
- **cooking zone power n°x Kw : 6 x 2.6 ;**
- voltage and work control lights;
- **static electric oven** entirely made of **stainless steel** , with **4-level supports for GN 2/1 grids/trays ( 530x650 mm);**
- **grill with salamander function** in the upper part and **thermostat** that allows accurate **temperature regulation from 50 to 270 °C;**
- **line indicator and temperature indicator ;**
- **oven power kW 7.5 ;**
- **line indicator and temperature indicator ;**
- door and inner door pressed in AISI 304 stainless steel;
- high-resistance door handle in 20/10 thick AISI 304 steel;
- adjustable feet;
- **2 year warranty .**

**Supplied :**

- 1 anti-tipping oven rack

**Accessories/Options :**

- compartment door

CE mark  
Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
BS-E7P6+FE	ELECTRIC COOKER 6 PLATES on ELECTRIC OVEN GN 2/1, BERTOS, MACROS 700 line, HIGH POWER Series, with 6 ROUND plates Ø 220 mm, INDEPENDENT CONTROLS, 6 power levels, V.400/3+N, Kw.23, 1, weight 129 kg, dim.mm.1200x700x900h	



macros 700



HIGH POWER

2,6 kW	2,6 kW	2,6 kW	► Ø 220 mm
2,6 kW	2,6 kW	2,6 kW	



GN 2/1  
530 x 650 mm x 4 pos.



macros 700

	n.	6
	Ø mm	220
	kW	2,6
	GN	2/1
	kW	7,5 (4,5 + 3)
	mm	530 x 650 x 4 pos.
		380 - 415 V3N~
	TOT. kW	23,1



