



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Trifase
Volts	V 400/3 +N
frequency (Hz)	50
net weight (Kg)	100
breadth (mm)	800
depth (mm)	700
height (mm)	900

PROFESSIONAL DESCRIPTION

ELECTRIC COOKER 4 INFRARED ZONES on ELECTRIC OVEN GN 2/1, MACROS 700 Line, INFRARED Series :

- **worktop and front panels in AISI 304 stainless steel ;**
- **6 mm thick glass ceramic top ;**
- **electrical resistors capable of reaching high temperatures (500 °C) heat the hob by radiation ;**
- **the areas are highlighted by special silk-screen printing** which allows correct positioning of the pans;
- **4 square zones of 230 x 230 mm each ;**
- **cooking zone power n° x Kw: 4 x 3.2 ;**
- **after each individual zone is turned off, a light signals the residual heat up to 60 °C , to safeguard the operator's safety;**
- **static electric oven** entirely made of **stainless steel** , with **4-level supports for GN 2/1 grids/trays (530x650 mm) ;**
- **grill with salamander function** in the upper part and **thermostat** that allows accurate **temperature regulation from 50 to 270 °C ;**
- **oven power 7.5 kW ;**
- **line indicator and temperature indicator ;**
- **door and inner door pressed in AISI 304 stainless steel;**
- **high-resistance door handle in 20/10 thick AISI 304 steel;**
- **adjustable feet;**
- **2 year warranty .**

Supplied :

- 1 anti-tipping oven rack

CE mark

CODE	DESCRIPTION	PRICE/DELIVERY
BS-E7P4/VTR+FE	ELECTRIC COOKER 4 INFRARED ZONES on ELECTRIC OVEN GN 2/1, BERTOS, MACROS 700 line, INFRARED Series, with 4 SQUARE zones measuring 230x230 mm, INDEPENDENT CONTROLS, V.400/3+N, Kw.20.3, Weight 100 Kg, dim.mm.800x700x900h	






macros 700

INFRARED





INFRARED

3,2 kW	3,2 kW	▶ 230x230 mm
3,2 kW	3,2 kW	


FE





7,5 kW

GN 2/1


530 x 650 mm x 4 pos.









macros 700

INFRARED




	n.	4
	mm	230 x 230
	kW	3,2



	GN	2/1
	mm	530 x 650 x 4 pos.
	kW	7,5 (4,5+3)

380 - 415 V3N~

	TOT.	kW	20,3
---	------	----	------

900
35 3/8"

700
27 1/2"

800
31 1/2"

