



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,34
net weight (Kg)	7,5
breadth (mm)	377
depth (mm)	265
height (mm)	160

PROFESSIONAL DESCRIPTION

PROFESSIONAL VACUUM MACHINE with EXTERNAL SUCTION with 340 mm SEALING BAR :

- **body in satin stainless steel ;**
- automatic lid lifting;
- **vacuum indicator** : analog vacuum gauge with anti-vibration needle 0 / -1 bar;
- **decompression chamber emptying solenoid valve ;**
- double decompression seal gasket: top - bottom;
- **external suction impurity filter ;**
- **microprocessor control electronic board** , interchangeable with manually detachable connector;
- standby function after 300 seconds;
- **air intake for vacuum packing in containers ;**
- **guide stop for positioning the envelope .**

VACUUM PUMP :

- **dry self-lubricating with thermostatic protection ;**
- **noise silencer ;**
- maximum depression: - 0.8 bar Q = 11 l/min \pm 10%;
- Motor power: 85 W .

WELDING BAR :

- **welding : 5 mm x 340 mm with canvas impression ;**

- post-weld cooling cycle;
- **automatic temperature compensation;**
- structure entirely in Bakelite;
- Power: 340/405 W.

CE mark
Made in ITALY

CODE	DESCRIPTION	PRICE/DELIVERY
TCF454-000100	Professional vacuum packaging machine with external suction, 340 mm sealing bar with 5 mm wide sealing, vacuum indicator, external suction impurity filter, V.230/1, Kw.0.34, Weight 7.5 Kg, dim.mm.377x265x160h	€ 270,42 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

