

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



## **TECHNICAL CARD**

breadth (mm)	245
depth (mm)	340
height (mm)	485

## PROFESSIONAL DESCRIPTION

## SEMI-AUTOMATIC CABIN WATER SOFTENER, with MANUAL ACTIVATION OF REGENERATION VIA BUTTON:

Max flow rate: 500 LT/H
Min Pressure: 1.5 ATE
Max Pressure: 7 ATE

• Water Temperature min - max : 2 - 35 °C

• Inlet - Outlet connection : 3/8 M

• Exhaust Connection : HOSE HOLDER DIAM.14 MM

• Regeneration Duration : 22' MINUTES

 $\circ~$  Quantity of salt consumed during regeneration : 0.8 KG.

• Hardness Mixing System : Yes

Limescale is the main cause of all the problems of blockages and damage to pipes , taps , coils , boilers and of a notable increase in energy consumption that we often don't realize. The advantages derived from the use of softened water are concrete and tangible .

The MATIC MANU 8 mod. water softener has been designed to meet the needs of those who supply equipment for bars , large kitchens , restaurants , hotels and manufacturers or traders of coffee machines , roasters, ovens and dishwashers .

The main features of this softener are its **extremely small size**, its **compactness**, **suitable for installation in minimal spaces** and the **ease of carrying out the regeneration** which, combined with an application downloadable on APPLE and ANDROID, allows the regeneration to be carried out correctly and within the indicated times, without wasting time.

IDEAL FOR CONNECTING :

Ideal for convection ovens

Or:

N.1 2-group coffee machine

CE MARK

CODE	DESCRIPTION	PRICE/DELIVERY
TH-MATICMANU8	Semi-automatic cabinet purifier/softener, manual activation of regeneration via button, max flow rate 500 l/h, dim.mm.245x340x485h	€ 221,04  VAT escluded  Shipping to be calculed
		<b>Delivery</b> from 8 to 15 days