



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,235
net weight (Kg)	72
gross weight (Kg)	87
breadth (mm)	900
depth (mm)	700
height (mm)	970

PROFESSIONAL DESCRIPTION

REFRIGERATED **SALADETTE 2 DOORS** for **SALADS**, worktop designed for **5 GN 1/6 CONTAINERS** :

- **external structure in stainless steel** ;
- **worktop in food-grade polyethylene** ;
- **lid with telescopic opening** ;
- capacity 240 lt;
- **temperature + 2 ° / + 8 ° C** ;
- **electronic thermostat** ;
- 1 intermediate grid for GN1 / 1 door;
- **Static refrigeration** ;
- automatic defrost at standstill;
- **static evaporator foamed on three sides with fan** to uniform the temperature;
- **ECOLOGICAL R600a refrigerant gas** ;
- automatic evaporation of condensation water;
- max ambient temperature / humidity: + 35 ° C / 50% HR;
- insulation thickness 40 mm;
- internal dimensions mm 827x512x500h.

Supplied:

- 2 Gastro-norm 1/1 grids ;



NB : Gastro-norm TRAYS EXCLUDED

CE MARK

Made in ASIA

CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-PS200-FC	Refrigerated saladette for salads with 2 DOORS, capacity 5 GN 1/6 pans, Temp. + 2 ° / + 8 ° C, ECOLOGICAL Gas R600a, V.230 / 1, Kw.0,235, Weight 72 Kg, dim.mm 900x700x970h	€ 605,64 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
IK54516 	18/10 stainless steel lid with handle grip for GN 1/6 container	€ 4,96 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
FC-CS12-FC 	Set of 2 drawers	€ 250,50 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days