



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,235
net weight (Kg)	80
gross weight (Kg)	98
breadth (mm)	900
depth (mm)	700
height (mm)	850

PROFESSIONAL DESCRIPTION

REFRIGERATED TABLE with 4 DRAWERS, capacity 220 litres, Temp.+2°/+10°C, Gastro-Norm 1/1:

- external structure in stainless steel ;
- work surface in food-grade polyethylene ;
- telescopic opening lid ;
- capacity 220 litres;
- 1 intermediate grill for GN 1/1 door;
- compartments suitable for inserting Gastro-Norm 1/1 grills or trays (530x325 mm);
- temperature +2°/+10°C;
- electronic thermostat ;
- static refrigeration ;
- automatic defrost when off ;
- automatic evaporation of condensation water ;
- static evaporator foamed on three sides with fan to uniform the temperature;
- ECOLOGICAL refrigerant gas R600a ;
- maximum ambient temperature : +35°C;
- maximum temperature humidity : 50% HR;
- insulation thickness 40 mm;
- internal dimensions 827x512x500h mm.

Supplied:
◦ 4 drawers

CE MARK

CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-S9014D-FC	Refrigerated Table with 4 Drawers, Professional, capacity 220 litres, Temperature +2°/+10°C, Static refrigeration, Gastro-Norm 1/1, Gas R600a, V.230/1, Kw.0,235, Weight 80 Kg, dim.mm.900x700x850h	€ 985,54 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days

