

**TECNOSERVICE'21 srl**

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973

**TECHNICAL CARD**

net weight (Kg)	57
gross weight (Kg)	79
breadth (mm)	1020
depth (mm)	520
height (mm)	925

PROFESSIONAL DESCRIPTION**PREFABRICATED COLD ROOM SUPEREKO line for normal temperatures -2° +8°C :**

- **made with modular sandwich panels** , 70 mm thick, in **non-toxic white pre-painted sheet metal** , insulated with **high density polyurethane** , 40-42 kg/cubic meters (95% closed cells)
- **Panel locking** using eccentric hooks;
- **revolving door with clear light in the following sizes:** 600x1850 mm, 700x1850 mm, 800x1850 mm, 900x1850 mm;
- easily adjustable door hinges in 3 directions;
- **handle with lock and safety release from the inside** in phosphorescent material;
- **PED pedestrian flooring made of non-slip AISI 304 stainless steel sheet, STATIC LOAD CAPACITY 1500 Kg/m², POINT LOAD CAPACITY 100 Kg;**
- **rounded internal corners** for **maximum hygiene** and **ease of cleaning** ,
- **internal light** ,
- provision for **micro door** ,
- prepared for a monoblock **refrigeration unit overlapped on the wall** ,
- on request it is possible to install **ceiling -mounted monoblock units** or **refrigeration units with remote group** ,
- supplied disassembled and packed on pallets (on request on cages)
- **net capacity : 3.8 cubic meters** ,
- **working temperature : -2° +8°C** ,
- **INTERNAL DIMENSIONS** : mm 1200x1600x200h.
- **EXTERNAL DIMENSIONS:** mm 1340x1740x2140h

Accessories:

- Internal shelving made of 20 micron anodized aluminum with 3 rows of grilled shelves.
- Crawl space for floor ventilation made of plastic profile.

- Door curtain made of transparent plastic strips
- Door microswitch.

Optional on request:

- Driveable and reinforced floor
- Ceiling refrigeration units
- Split refrigeration systems (remote)
- Possibility of measures other than those proposed.

ICE-LAIKA - TN
OVERLAPPED MONOBLOCK REFRIGERATION UNIT
V. 230/1 - Kw 1,8

- External bodywork of the monoblock in **galvanized sheet metal**;
- evaporator part frame in magnesium aluminum;
- **max operating ambient temperature +38°C**
- **ECOLOGICAL REFRIGERANT GAS** R452a
- hermetic compressor;
- Automatic saving high and low pressure switch
- automatic hot gas defrosting
- siphon on the condensate drain
- power cable for door resistor;
- cable for micro port connection;
- digital telethermometer display with temperature indication and operating status display: cold-defrosting-evaporator fans-alarm in progress.
- possibility of displaying alarms such as: high and low temperature and pressure, open door, condensation, dirt, etc.
- provision for connection to the frigotel supervisor

CE mark
Made in ITALY

CODE	DESCRIPTION	PRICE/DELIVERY
TCF474-L09125N	Monobloc wall-mounted TN refrigeration unit, tropicalized, for normal temperature -2°+8°, ventilated, with ecological gas R404a, V 230/1, Kw 1.3, weight Kg 57, external dimensions mm 1020x520x925h	<div> <div>€ 1.937,36</div> <div>VAT excluded</div> <div>Shipping to be calculated</div> </div> <div> Delivery from 8 to 15 days </div>