

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



net weight (Kg)	58
gross weight (Kg)	80
breadth (mm)	1020
depth (mm)	520
height (mm)	925

PROFESSIONAL DESCRIPTION

PREFABRICATED COLD ROOM SUPEREKO line for normal temperatures -2° +8°C :

- made with modular sandwich panels , 70 mm thick, in non-toxic white pre-painted sheet metal , insulated with high density polyurethane , 40-42 kg/cubic meters (95% closed cells)
- Panel locking using eccentric hooks;
- revolving door with clear light in the following sizes: 600x1850 mm, 700x1850 mm, 800x1850 mm, 900x1850 mm;
- easily adjustable door hinges in 3 directions;
- $\circ \ \ \textbf{handle with lock} \ \text{and } \textbf{safety release from the inside} \ \text{in phosphorescent material}; \\$
- PED pedestrian flooring made of non-slip AISI 304 stainless steel sheet, STATIC LOAD CAPACITY 1500 Kg/m², POINT LOAD CAPACITY 100 Kg;
- rounded internal corners for maximum hygiene and ease of cleaning ,
- internal light ,
- provision for micro door,
- o prepared for a monoblock refrigeration unit overlapped on the wall,
- on request it is possible to install ceiling -mounted monoblock units or refrigeration units with remote group ,
- supplied disassembled and packed on pallets (on request on cages)
- o net capacity: 3.8 cubic meters,
- working temperature : -2° +8°C ,
- INTERNAL DIMENSIONS : mm 1200x1600x200h.
- EXTERNAL DIMENSIONS: mm 1340x1740x2140h

Accessories:

- Internal shelving made of 20 micron anodized aluminum with 3 rows of grilled shelves.
- Crawl space for floor ventilation made of plastic profile.

- o Door curtain made of transparent plastic strips
- o Door microswitch.

Optional on request:

- Driveable and reinforced floor
- · Ceiling refrigeration units
- Split refrigeration systems (remote)
- o Possibility of measures other than those proposed.

ICE-LAIKA - TN OVERLAPPED MONOBLOCK REFRIGERATION UNIT V. 230/1 - Kw 1,8

- External bodywork of the monoblock in galvanized sheet metal;
- o evaporator part frame in magnesium aluminum;
- max operating ambient temperature +38°C
- ECOLOGICAL REFRIGERANT GAS R452a
- hermetic compressor;
- Automatic saving high and low pressure switch
- o automatic hot gas defrosting
- siphon on the condensate drain
- power cable for door resistor;
- cable for micro port connection;
- digital telethermometer display with temperature indication and operating status display: cold-defrosting-evaporator fans-alarm in progress.
- o possibility of displaying alarms such as: high and low temperature and pressure, open door, condensation, dirt, etc.
- o provision for connection to the frigotel supervisor

CE mark Made in ITALY

CODE	DESCRIPTION	PRICE/DELIVERY
TCF474-L09125N	Monobloc wall-mounted TN refrigeration unit, tropicalized, for normal temperature -2°+8°, ventilated, with ecological gas R404a, V 230/1, Kw 1.3 - weight Kg 57, external dimensions mm 1020x520x925h	€ 1.937,36 VAT escluded Shipping to be calculed Delivery from 8 to 15 days