



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,18
net weight (Kg)	59
gross weight (Kg)	70
breadth (mm)	910
depth (mm)	510
height (mm)	550

PROFESSIONAL DESCRIPTION

REFRIGERATED DISPLAY CASE in STAINLESS STEEL, capacity 110 l, Class C:

- structure in **18/10 stainless steel** ;
- **ventilated refrigeration** ;
- timed defrost with self-evaporator condensate collection tray;
- **electronic temperature control**;
- **sliding doors** from both sides;
- operating temperature: **+2°/+8° C** ;
- **R600a ECOLOGICAL gas** ;
- **energy class C** ;
- internal LED light;
- the entire glazed part made of double insulating glass.

Operating environmental conditions :

- Ambient Temperature Max 28°C.
- Relative Humidity 60 %

Included :



- n°1 grid dim. mm. 552x390h.

OPTIONALS/ACCESSORIES:

- chromed grille Code FOGRC91.
- hooking set for grates Cod. FOAG.

CE mark

CODE	DESCRIPTION	PRICE/DELIVERY
FO-G-HAV91	Refrigerated counter display case in stainless steel, VENTILATED refrigeration, temperature +2°/+8° C, capacity lt.110, ECOLOGICAL Gas R600a, Class C, V.230/1, Kw 0,18, Weight 59 Kg, dim . external mm. 910x510x550h	€ 668,96 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days

TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
FOAG 	Clamping set for grids	€ 5,84 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
FOGRC91 	Chromed grid	€ 25,77 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

