



#### TECHNICAL CARD

<b>net weight (Kg)</b>	34
<b>gross weight (Kg)</b>	45
<b>breadth (mm)</b>	680
<b>depth (mm)</b>	560
<b>height (mm)</b>	610

#### PROFESSIONAL DESCRIPTION

**Gravity slicers** in aluminum alloy with **gear transmission**, **blade diameter 300 mm** - available in **single-phase or three-phase** version .

- Blade diameter 300 mm;
- With **a wide base** , ideal for any type of shop or supermarket.
- The **gear transmission is very reliable** , **resistant to stress** , and **allows even the hardest product to be cut** .
- The gear transmission, in fact, is able to satisfy even the **most demanding customers** , eliminating several problems: that of the wear of the belt, that of the need for continuous maintenance and adjustment of the belt itself and finally those that can sometimes occur due to the slipping of the belt.
- Trolley stroke mm 290
- Blade revolutions n.220 per minute;
- Cutting regulator mm 14
- Cutting capacity Ø mm 215 - mm 215X270
- **ALSO AVAILABLE IN A LONG STROKE VERSION**, with a larger base, for better cutting capacity.

**CE mark**  
**Made in Italy**

#### AVAILABLE MODELS

**TCF205-000700**

**Gravity slicers in aluminum alloy with gear transmission, blade diameter mm 300, weight 34 Kg, V.230/1, kw 0.3, dim.mm 680x560x610h**

**€ 1.212,93**

*VAT excluded*  
*Shipping to be calculated*

**Delivery** from 10 to 18 days



**TCF205-000710**



**Gravity slicers in aluminum alloy with gear transmission, blade diameter mm 300, weight 34 Kg, V.400/3, kw 0.33, dim.mm 680x560x610h**

**€ 1.212,93**

*VAT excluded*

**Shipping to be calculated**

**Delivery** from 10 to 18 days

