



#### TECHNICAL CARD

<b>net weight (Kg)</b>	38
<b>gross weight (Kg)</b>	50
<b>breadth (mm)</b>	680
<b>depth (mm)</b>	560
<b>height (mm)</b>	610

#### PROFESSIONAL DESCRIPTION

**Gravity slicers** in aluminum alloy with **gear transmission**, **blade diameter 330 mm** - available in **single-phase or three-phase** versions

- **Blade diameter** 330 mm;
- With a **wide base**, ideal for any type of shop or supermarket.
- The **gear transmission is very reliable**, **resistant to stress**, and **allows even the hardest product to be cut**.
- The gear transmission, in fact, is able to satisfy even the **most demanding customers**, eliminating several problems: that of belt wear, that of the need for continuous maintenance and adjustment of the belt itself and finally those that can sometimes occur due to belt slippage.
- **Trolley stroke** 290 mm
- **Cutting Regulator** mm 14
- **Blade revolutions** n.220 per minute;
- **Cutting capacity** Ø mm 230 - mm 230x255
- **ALSO AVAILABLE IN A LONG STROKE VERSION**, with a larger base, for better cutting capacity.

**CE mark**  
**Made in Italy**

#### AVAILABLE MODELS

**TCF205-000750**

**Gravity slicers in aluminum alloy with gear transmission, blade diameter 330 mm, weight 38 kg, V.230/1, kw 0.3, dim. mm 680x560x610h**

**€ 1.283,12**

*VAT excluded*  
**Shipping to be calculated**

**Delivery** from 10 to 18 days



**TCF205-000760**



**Gravity slicers in aluminum alloy with gear transmission, blade diameter 330 mm, weight 38 kg, V.400/3, kw 0.33, dim. mm 680x560x610h**

**€ 1.283,12**

*VAT excluded*

**Shipping to be calculated**

**Delivery** from 10 to 18 days

