



PROFESSIONAL DESCRIPTION

SOOT REMOVAL for WOOD OVENS and GRILLS :

- made of **304 Aisi 18/10 stainless steel** , 15 mm thick,
- **automatic operation with water fume treatment** ,
- filtering with G2 755 micro-stretched mesh filters,
- **water tank control** and distribution **via automatic float** ,
- high pressure stainless steel water pump, heat resistant 110°C,
- **shatterproof, explosion-proof control panel** .
- **NB- IMPORTANT :**
- The flue, downstream (...outgoing) of the machine, **must be watertight** , as the condensation that will form inside will have to **return/fall** either **inside the tank of the machine itself** , or conveyed into a drain.
- The machine, in addition to breaking down soot, creates a ' **draught effect** ' helping **the expulsion of fumes** from the outgoing flue.
- If the flue is **particularly long** , winding and it is **necessary to use an extractor** , it is important to maintain the air speed in the flue within certain parameters that will be provided by the manufacturer.

MADE IN ITALY

AVAILABLE MODELS

MZAGF/200



Stainless steel soot remover for wood-fired ovens and grills, CAPACITY 250-500 m3/h, V 230/1, kw 0.75, dim. mm 1000x650x850h

€ 3.039,43

VAT excluded

Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/250

Stainless steel soot remover for wood ovens and grills, CAPACITY 400-800 m3/h, V 230/1, kw 0.75, dim. mm 1000x650x850h

€ 3.584,00

VAT excluded

Shipping to be calculated

Delivery from 8 to 15 days



MZAGF/300T



Stainless steel soot remover for wood ovens and grills, CAPACITY 1000-2000 m3/h, V 380/3, kw 1.5, dim. mm 1150x750x950h

€ 4.005,26

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/300



Stainless steel soot remover for wood ovens and grills, CAPACITY 1000-2000 m3/h, V 230/1, kw 1.5, dim. mm 1150x750x950h

€ 4.005,35

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/400



Stainless steel soot remover for wood-fired ovens and grills, CAPACITY 2500-4500 m3/h, V 230/1, kw 3, dim. mm 1300x1150x1450h

€ 8.181,18

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/400T



Stainless steel soot remover for wood ovens and grills, CAPACITY 2500-4500 m3/h, V 380/3, kw 3, dim. mm 1300x1150x1450h

€ 8.181,18

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/500



Stainless steel soot remover for wood-fired ovens and grills, CAPACITY 4000-7000 m3/h, V 230/1, kw 4, dim. mm 1600x1250x1450h

€ 11.619,77

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/500T



Stainless steel soot remover for wood ovens and grills, CAPACITY 4000-7000 m3/h, V 380/3, kw 4, dim. mm 1600x1250x1450h

€ 11.619,77

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZAGF/600T



Stainless steel soot remover for wood ovens and grills, CAPACITY 5000-9000 m3/h, V 380/3, kw 5.5, dim. mm 1600x1250x1450h

€ 12.668,03

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

TECHNICAL CARD

CODE/PICTURES

DESCRIPTION

PRICE/DELIVERY

MZ-EVAGF/1

Exhaust solenoid valve

€ 516,06

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days



MZ-CPG/200



Soundproof outdoor cover

€ 757,46

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-CPG/250



Soundproof outdoor cover

€ 757,46

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-EVAGF/2



Exhaust solenoid valve

€ 758,21

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-CPG/300



Soundproof outdoor cover

€ 894,68

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-CPG/400



Soundproof outdoor cover

€ 1.620,29

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-CPG/500



Soundproof outdoor cover

€ 2.669,63

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days

MZ-CPG/600



Soundproof outdoor cover

€ 2.669,63

VAT excluded
Shipping to be calculated

Delivery from 8 to 15 days



Abbattitori di fuliggine con possibilità di installazione interna

ART.	PORTATA MCH	CAPACITÀ RISERVA ACQUA LT	% ABBATTIMENTO			POTENZA ASSORBITA		Volt	Ø CANALE INGRESSO FUMI Ø CANALE USCITA FUMI	DIMENSIONI mm
			CO	CO ₂	polveri mg/Nm	Kwh/H - A				
AGF/200	250 - 500	80	82%	30%	40%	0,75	HP-5,6 A	230 V	200 mm	1000x650x850
AGF/250	400 - 800	80	82%	30%	40%	0,75	HP1-5,6 A	230 V	250 mm	1000x650x850
AGF/300	1000 - 2000	120	82%	30%	40%	1,5 1,5	HP2-7 A HP2-4 A	230 V 320 V	300 mm	1150x750x950
AGF/350	1500 - 3500	120	82%	30%	40%	1,85 1,85 1,85	HP2,5-10,7 A HP2,5-8,2 A HP2,5-4,8 A	230 V 230 T 380 T	350 mm	1150x750x950
AGF/400	2500 - 4500	350	82%	30%	40%	3 3	HP4-9,7 A HP4-5,6 A	230 V 380 T	400 mm.	1300x1150x1450
AGF/500	4000 - 7000	350	82%	30%	40%	4 4	HP5,5-14,7 A HP5,5-8,5 A	230 V 380 T	500 mm ingresso 600 mm uscita	1600x1250x1450
AGF/600	5000 - 9000	350	82%	30%	40%	5,5	HP7,5-12 A	380 T	600 mm ingresso 900 mm uscita	1600x1250x1450

