



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	5060
motor power capacity (Kw)	0,9
net weight (Kg)	60
breadth (mm)	510
depth (mm)	560
height (mm)	450

PROFESSIONAL DESCRIPTION

COUNTER BELL VACUUM PACKAGING MACHINE, SYSTEM Line with DIGITAL CONTROLS :

- **New series** of digital counter top packaging machines;
- Equipped with **brand new electronic card** ;
- **Digital control panel with 3** editable and customizable programs;
- **1 program for marinating meat** ;
- **400 mm sealing bar** with completely renewable wiring;
- Pump self- **cleaning / heating system** for optimal management of the packaging machine, reducing maintenance times and costs;
- **GASTROVAC function** for creating external vacuum in GN containers;
- **EXTRAVAC function** , which offers a **second vacuum phase lasting 5 seconds** (particularly suitable for minced and boned meat);
- Quick stop / welding;
- Carter with 90 ° opening to facilitate access to the inside of the packaging machine;
- **Vacuum chamber 410x450x220h mm** , made of stainless steel molded in a single piece with rounded corners for maximum hygiene and easy cleaning;
- **20 meters / cubic / hour vacuum pump** ;
- **Simple and immediate electronics** , 18-level sealing for any type of bag;
- **Note** : Possibility of **external vacuum** with **the use of embossed envelopes** , (as shown in the photo).

OPTINAL / ACCESSORIES:


- Possibility of **vacuuming in external containers** or **gastro-norm basins** using a special kit - Code EMATUBOGN.
- Predisposition for **inert gas kit** - Code EMGASINERTE.

- Sealing **bar with piston lifting** - Code EMBSP.
- Sealing **bar with envelope excess cut (scrap)** - Cod. EMTS.
- Bell stop bar - Code EMBF.
- Inclined plane for liquid packaging - Code EMPI.
- Machine support trolley - Code EMCR.


CE mark
Made in Italy


CODE	DESCRIPTION	PRICE/DELIVERY
EM-SYSTEM40	BELL VACUUM PACKAGING MACHINE for counter, SYSTEM Line, CHAMBER mm. 410x450x220h, 400 mm WELDING BAR, 20 m / cubic / hour VACUUM PUMP, V.230 / 1, Kw. 0.90, Weight Kg. 60, external dimensions mm.510x560x450h	€ 1.858,71 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days


TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY


EM-BF	TECHNOCHEF - Bell holder, Mod.BF	€ 24,99 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
		

EM-BSPVE	Sealing bar with piston	€ 79,61 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
		

EM-PI	Inclined plane, Mod.PI	€ 85,74 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
		

EM-TUBOGN	Tube with adapter sleeve in gastro containers	€ 102,01 <i>VAT excluded</i> Shipping to be calculated Delivery
		

EM-GSR	Gas inert, Mod.GSR	€ 242,57 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
		

EM-CR	Machine Support Trolley, Mod.CR	€ 282,20 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
		




STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA


STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello digitale
Digital panel



Sistema autopulizia olio
Oil made auto cleaning system



Pannello comandi a totale tenuta
contro umidità
Waterproof control Panel



Carter apribile a 90°
90° openable carter



Barre saldanti estraibili
Removable sealing bars



Vasca inox con angoli stondati
senza saldature
Entirely printed stainless steel
vacuum chamber, with internal
round corners



Connessione per attacco gastrovac
Connection for the gastrovac system



Set tavole di riempimento in
polietilene
Polyethylene filling squares set



OPTIONAL PER CONFEZIONATRICI A CAMPANA

OPTIONALS ONLY FOR CHAMBER MACHINES



Installazione gas inerte
Arrangement for idle gas



Vasca doppia altezza per
confezionamento liquidi (SYSTEM 408)
Special double height vacuum chamber
to pack liquids (SYSTEM 408)



Pompa Busch
Busch Pump



Saldatura con pistoni senza cavi
Sealing with cableless pistons



Tensione e frequenza speciale
Voltage and special frequency



Carrello supporto macchina
Chariot on wheels



Taglio Eccedenza
Exceeding cutting bar



Sistema bloccaggio campana
Lid Hook



Piano inclinato per liquidi
Inclined plane for liquids

Modifica parametri vuoto / saldatura / tempo immissione gas
 - Attivazione / Disattivazione GAS INERTE
used to modify vacuum/sealing/gas injection time parameters
 - connection/disconnection of inert gas

Funzione Gas Inerte
 Attivata (LED ACCESO)
Inert gas function on (LED on)

1. Settaggio % di vuoto
 2. Settaggio tempo di saldatura
 3. Attivazione funzione saldatura rapida
 4. Attivazione funzione VAC STOP:
 interruzione anticipata del ciclo di vuoto
- 1. Setting of the vacuum percentage*
2. Setting of the sealing time
3. Activation of RAPID SEALING, if you push the button once
4. Activation of VAC STOP FUNCTION (stop in advance the vacuum cycle) if you push the button twice



Accensione / Spegnimento
 confezionatrice
switch on / switch off of the vacuum packaging machine

Funzione di vuoto in
 continuo, per aspirazione
 in contenitori gastro
nonstop vacuum function done with suction in gastro bowls

Definizione della percentuale di
 vuoto raggiunta in camera
vacuum level reached in the chamber

Funzione di pulizia olio pompa del
 vuoto.
 Premendo il tasto per tre secondi
 a campana chiusa
pushing the button for three seconds (only when the bell is closed) the cleaning function of the vacuum pump begins

Definizione tempo di saldatura
 (espresso in secondi)
sealing time (in seconds)