



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
ITF-LCC/I	MODULAR electric pizza oven, for 8 pizzas diam. 300 mm, version with STAINLESS STEEL FRONT, CHAMBER COMPLETELY in REFRACTORY mm 600x1200x170h, V.400/3, Weight 200 Kg, Kw.8,5, external dimensions mm 1000x1560x400h	€ 4.036,39 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days
PROFESSIONAL DESCRIPTION		

ELECTRIC PIZZA OVEN , MODULAR, Modular for 8 PIZZAS :

- version with **stainless steel front** ,
- **COOKING CHAMBER TOTALLY in REFRACTORY** measuring **600x1200x170h mm**, with high-performance and resistant cooking surface and ceiling,
- **loading capacity per room: 8 PIZZAS diam. 300 mm** or **3 600x400 mm trays** ,
- vapor exhaust on the back of the chamber,
- **“hy-pe” stainless steel armored heating elements** integrated into the refractory of the hob and the ceiling,
- **digital control panel as standard** ,
- **independent commands** for each room,
- **separate digital adjustment of the top and hob power** ,
- **thermal insulation** ,
- **maximum cooking temperature 450 °C** ,
- adjustable valve for steam exhaust,
- **Armored NEEDLE resistors inserted 1 for each hole of the REFRACTORY** of the top and bottom, **ensure maximum UNIFORMITY of TEMPERATURE** ,...at the same time being **EASILY REPLACEABLE INDIVIDUALLY** from the back **without dismantling the Refractory**,
- door with **tempered glass window** ,
- counterbalanced front doors,
- **halogen lamps** with high resistance and light capacity.

Accessories/Options:



- **oven supports** with **tray holder guides** made of painted steel, available with **heights** of **500 mm, 700 mm** and **860 mm**,
- **leavening cells** for monobloc ovens, available with stainless steel or rustic front
- electric heating **with thermostatic control (temp. 0°/+90°C)** available with **heights** of **500 mm** and **700 mm** to adapt to modules with 1 or 2 chambers,
- **feet for leavening cells**
- **single hood module with stainless steel front** ,
- **4 wheel kit**, 2 of which with brake.

MADE IN ITALY

TECHNICAL CARD

power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	8,5
net weight (Kg)	200
breadth (mm)	1000
depth (mm)	1560
height (mm)	400

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
ITF-PPD 	Feet for leavening cells Feet for leavening cells (h min 8 / max 20 cm)	€ 76,71 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
ITF-KRF 	4 wheel kit Kit 4 wheels, 2 of which with brake (h 16 cm)	€ 189,62 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days

ITF-KCC**Unique hood module with rustic front**

Single hood module with rustic front for ovens mod. LCC / I and LCC / R, dim.mm.1000x1730x160h

€ 479,43*VAT excluded***Shipping to be calculated****Delivery** from 8 to 15 days**ITF-SCCC****UNICO painted steel support for oven**

UNICO painted steel support for oven Mod. LCC / I and LCC / R, dim.mm.1010x1560x860h

€ 492,62*VAT excluded***Shipping to be calculated****Delivery** from 8 to 15 days**ITF-BCC/I****Leavening cell with stainless steel front**

Proving room for oven Mod. LCC / I version with stainless steel front, electric heating with thermostatic control (temp.0 ° / + 90 ° C), V.230 / 1, Kw.1.00, dim.mm.1000x1560x700h

€ 1.468,56*VAT excluded***Shipping to be calculated****Delivery** from 4 to 9 days



Modulo cappa



Camera cottura cm 60x120x17h



Camera cottura cm 60x120x17h



Camera cottura cm 60x120x17h



Supporto aperto per forno



Modulo cappa

KCC - dim.mm.1000x1730x160h

Modulo cottura camera

LCC/I - dim.mm.600x1200x170h

Cella di lievitazione

BCC - dim.mm.1000x1260x700h



EURO / CL

Forno elettrico modulare per pizzeria, pasticceria e panetteria. Disponibile in versione CLASSIC e STAND. Possibilità di inserire la "vaporiera" su ogni camera di cottura.



CL



PANNELLO COMANDI DIGITALE



Regolazione separata potenza cielo e piano di cottura

EFFICIENCY & TECHNOLOGY



450° 450°C DI TEMPERATURA MASSIMA DI COTTURA



ISOLAMENTO TERMICO GARANTITO



VALVOLA REGOLABILE PER SCARICO VAPORI



MODULO CAPPA CON MOTORE E KIT
ABBATTIMENTO VAPORI E ODORI OPZIONALI

OPTIONAL




Camera di cottura totalmente rivestita in **materiale refrattario**.
Resistenze corazzate Hype inserite nel materiale refrattario.



CAPACITÀ DI CARICO PER CAMERA
LOADING CAPACITY PER DECK

LCC I/R **DIMENSIONI INTERNE**
LSC I/R Internal dimensions
A/H 17 x L/W 60 x P/D 120 cm
8 Pizze Ø 30 cm
3 Teglie 60x40 cm
3 Baking pans 60x40 cm



DATI TECNICI
TECHNICAL CHART



CL	Dimensioni interne (cm)			Dimensioni esterne (cm)			Peso	Alimentazione	Potenza	Potenza	Assorbimento	Temperatura	N° Teglie
	Internal dimensions (cm)			External dimensions (cm)			Weight	Supply	Power	Power	Absorption	Temperature	# Baking pans
	A/H	L/W	P/D	A/H	L/W	P/D	KG	V/Ph/Hz	KW	KW/h	Ampere	°C	60x40 cm
LCC / LSC I/R - DECK	17	60	120	40	100	156	200/165	400/3/50-60	8,3	4,5	13	0/450	
RCC / RSC - HOOD				16	100	173	37	230/1/50-60	0,3	0,3			
BCC / BSC - PROVER				70/50	100	156	90/75	230/1/50-60	1	0,5		0/90	28/12
SCCC / SCSC - STAND				86/70/50	101	156	52/47/40						16/6/6