

## TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



| CODE          | DESCRIPTION   | PRICE/DELIVERY |
|---------------|---|----------------|
| TCF163-000800 | MIXER with DEEP ARMS, with cast iron gears in oil bath, 70 lt. stainless steel bowl, 40 Kg mixing capacity, version with variable speed, V.400/3, Kw.2,2, Weight 270 Kg, dim.mm.600x770x1350h |                |

## PROFESSIONAL DESCRIPTION

## MIXER with PLUNGING ARMS, with 70 I STAINLESS STEEL BOWL, 40 Kg MIXING CAPACITY, version with VARIABLE SPEED:

- ideal for making high quality doughs for pizzerias and pastry shops, the use of the dipping arm system allows excellent oxygenation of the doughs;
- $\circ~$  movement of the arms made with cast iron gears in an oil bath ;
- **highly robust** and perfectly watertight **cast iron gearbox** , extremely silent mechanism;
- kneading arms made of AISI 304 stainless steel;
- <u>right arm adjustable in height</u> for making special pastry doughs (e.g. panettone);
- dough capacity: min.5 Kg / max.40 Kg (calculated with 55% hydration, the maximum capacity may vary according to the ingredients);
- $\circ~$  flour capacity : min.3 Kg / max.25 Kg ;
- 70 I stainless steel tank , diameter mm.530x320;
- variable speed : from 35 to 60 beats/minute;
- series timers ;
- $\circ \ \ \textbf{closed tank carter} \ \ \text{to prevent the flour from leaking out, made of highly robust transparent plastic;}$
- equipped with wheels for movement and two stabilizer feet .

## CE mark Made in Italy

| TECHNICAL CARD            |         |  |
|---------------------------|---------|--|
| power supply              | Trifase |  |
| Volts                     | V 400/3 |  |
| frequency (Hz)            | 50      |  |
| motor power capacity (Kw) | 2,2     |  |
| net weight (Kg)           | 270     |  |
| breadth (mm)              | 600     |  |
| depth (mm)                | 770     |  |



