

#### TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TD-TF02MIDBTAL	2 DOOR FREEZER/FREEZER TABLE with UPSTAND, TECNODOM brand, capacity lt.310, operating temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0,655, Weight 100 Kg, dim.mm.1420x715x950h	

## PROFESSIONAL DESCRIPTION

- 2 DOOR FREEZER/FREEZER TABLE with UPSTAND, capacity It.310, operating temperature -18°/-22°C:
- internal and external structure in Stainless Steel , with the exception of the external bottom in Galvanized Steel;
- rounded internal corners;
- $\circ \ \ \text{compartments suitable for inserting Gastro-Norm 1/1 grids or trays} \ (530x325 \ \text{mm}); \\$
- o capacity 310 liters;
- o perating temperature -18°/-22°C;
- $\circ \ \ \textbf{CFC-free polyurethane insulation} \ , \ injected \ at \ high \ pressure;$
- LV table insulation thickness: 60 mm;
- o doors with automatic closing and magnetic gasket;
- $\circ \ \textbf{electronic control instrument with 2 NTC probes} \ , \ \text{evaporator resistance, drain resistance, door edge resistance, thermostatic valve;}$
- ventilated refrigeration;
- removable and tropicalised monobloc refrigerating unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R404A/R507 gas;
- fully automatic defrosting and evaporation of condensed water;
- equipped with an insulating underlay;
- feet in stainless steel adjustable in height (110/190 H mm);
- o dim.mm.1420x715x850/1020.

### Included

• 1 Rilsan grid GN 1/1 and 2 L-shaped stainless steel guides per door

### CE mark Made in Italy

# **TECHNICAL CARD**

Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,655
net weight (Kg)	100
breadth (mm)	1420
depth (mm)	715
height (mm)	950