

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TD-TF04MIDBTAL	4 DOOR FREEZER/FREEZER TABLE with UPSTAND, TECNODOM brand, capacity lt.670, operating temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0,728, Weight 152 Kg, dim.mm.2320x715x950h	

PROFESSIONAL DESCRIPTION

FREEZER/FREEZER TABLE 4 DOORS with UPSTAND, capacity It.670, operating temperature -18°/-22°C, TECNODOM brand:

- internal and external structure in Stainless Steel, with the exception of the external bottom in Galvanized Steel;
- rounded internal corners ;
- compartments suitable for inserting Gastro-Norm 1/1 grids or trays (530x325 mm);
- o capacity 670 liters;
- o operating temperature -18°/-22°C;
- CFC-free polyurethane insulation , injected at high pressure;
- LV table insulation thickness: 60 mm;
- o doors with automatic closing and magnetic gasket;
- electronic control instrument with 2 NTC probes , evaporator resistance, drain resistance, door edge resistance, thermostatic valve;
- ventilated refrigeration;
- removable and tropicalised monobloc refrigerating unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R404A/R507 gas;
- $\circ\,$ fully automatic defrosting and evaporation of condensed water;
- $\circ\;$ equipped with an insulating underlay;
- $\circ\,$ feet in stainless steel adjustable in height (110/190 H mm);
- $\circ \ \, \text{dim.mm.} \\ 2320x715x950/1020.$

Included

o 1 Rilsan grid GN 1/1 and 2 L-shaped stainless steel guides per door

CE mark Made in Italy

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,728
net weight (Kg)	152
breadth (mm)	2320
depth (mm)	715
height (mm)	950