



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TD-AF14MIDMBT</b>	Freezer-Freezer Cabinet 2 doors, TECNODOM brand, stainless steel structure, capacity lt.1400, low temperature -18°/-22°C, ventilated refrigeration, Gastro-Norm 2/1, V.230/1, Kw.0 ,7, Weight 159 Kg, dim.mm.1420x800x2030h	<b>€ 1.874,91</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 25 to 35 days
PROFESSIONAL DESCRIPTION		

**2 DOOR FREEZER-FREEZER CABINET, 1400 lt capacity, operating temperature -18°/-22°C, TECNODOM brand :**

- **internal and external structure in stainless steel** except bottom, ceiling and external back in Galvanized Steel;
- rounded internal corners;
- **suitable for containing Gastro-Norm 2/1 grids or trays** (mm 650x530);
- capacity 1400 liters;
- operating temperature -18°/-22°C;
- CFC-free polyurethane insulation, injected at high pressure;
- **insulation thickness : 60 mm ;**
- self-closing doors with magnetic seal;
- **ventilation stop device when the door is opened ;**
- **front electronic control panel** with 2 NTC probes;
- evaporator resistance;
- **ventilated refrigeration ;**
- removable and tropicalised monobloc refrigerating unit as standard (ambient temperature +43°C and relative humidity of 65%);
- working with R404A/ R507 gas;
- **fully automatic defrosting and evaporation of condensed water ;**
- discharge resistance;
- door edge resistance;
- thermostatic valve;
- **feet in stainless steel adjustable in height** (110/190 H mm);
- dim.mm.1420x800x2030/2100h.

**Included :**

- 6 Rilsan plastic-coated grids GN 2/1
- 12 stainless steel guides
- fan stop

**CE mark**  
**Made in Italy**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,7
<b>net weight (Kg)</b>	159
<b>breadth (mm)</b>	1420
<b>depth (mm)</b>	800
<b>height (mm)</b>	2030