



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



TECHNOCHIEF.IT



FORCOLD

CODE	DESCRIPTION	PRICE/DELIVERY
FC-G-PZ3600TN-FC	REFRIGERATED PIZZA COUNTER with 3 DOORS, GRANITE top, temperature +2°/+8°C, ECOLOGICAL Ventilated in CLASS C, V 230/1, Kw 0,398, Weight 306 Kg, dim.mm.2020x800x1000h.	€ 1.113,91 <i>VAT excluded</i> Shipping to be calculated Delivery from 25 to 35 days
PROFESSIONAL DESCRIPTION		

PIZZA COUNTER 3 DOORS, with GRANITE WORKTOP and UPSTAND, operating temperature +2°/+8°C, ECOLOGICAL CLASS C, FORCOLD brand :

- **AISI 201 stainless steel structure ;**
- granite worktop with backsplash on 3 sides;
- **3 refrigerated compartments** capable of accommodating **600x400x70h mm roll holder boxes** ,
- operating temperature +2°/+8°C;
- **capacity lt.580 ;**
- **ventilated refrigeration ;**
- **ECOLOGICAL GAS R290 refrigerant ;**
- **Energy CLASS C ;**
- **removable built-in unit** for easy maintenance;
- front panel that can be opened with a key;
- **circular pattern of the cold air** so as not to directly touch the product;
- **electronic temperature control with digital thermostat ;**
- electrical resistance around the door frame for the elimination of condensation;
- **automatic defrosting** with electric heater and automatic defrosting temperature control;
- **automatic evaporation of condensed water ;**
- anti-corrosion treated evaporator;
- insulation thickness: 60 mm;
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- **height-adjustable stainless steel feet ;**
- possibility to lean against the wall.

- Included :**
- 7 Pairs of Door Runners (No Grid Supplied)

CE mark

TECHNICAL CARD	
power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,398
net weight (Kg)	306
breadth (mm)	2020
depth (mm)	800
height (mm)	1000

