



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
BS-G9TP+FG	GAS SOLID TOP COOKER on GN 2/1 GAS OVEN, BERTOS MAXIMA 900 line, HIGH POWER Series, total thermal power Kw. 20.8, weight 198 kg, dim.mm.800x900x900h	

PROFESSIONAL DESCRIPTION

GAS SOLID TOP COOKER on GN 2/1 GAS OVEN, MAXIMA 900 Line, HIGH POWER Series :

- **worktop and front and side panels in AISI 304 stainless steel ;**
- stainless steel interior;
- **central cast iron burner with optimized combustion , maximum power 13 kW , with thermocouple safety valve and pilot flame ;**
- **Thermal Zones x Power : 2 x 6.5 kW ;**
- **piezoelectric ignition** and combustion chamber lining in vermiculite, a high-performance insulating material;
- **high thickness steel plate with differentiated thermal zones** : maximum temperature in the center and decreasing towards the edges;
- the **internal lining , made of highly insulating refractory material** , allows **maximum concentration of heat in the central part** of the plate and guarantees great comfort to the Chef;
- perfectly smooth and **large surface plate** (760x750 mm) allows great freedom of use both with pans of unconventional shapes, even very large ones, and as a support surface next to the burners;
- **gas oven with flame burner** positioned under the enamelled hearth and thermostat adjustable from 160 to 280 °C;
- **oven power kW 7.8 ;**
- **capacity 4 GN 2/1 trays** (530x650 mm);
- **oven chamber in AISI 430** , with 4-level supports and pressed and ribbed stainless steel inner door;
- **internal fireplace in stainless steel** and burner support in AISI 430 stainless steel;
- high-resistance handle in AISI 304 stainless steel, thickness 20/10;
- **2 year warranty .**

Accessories/Options:

- grill for GN 2/1 kitchen oven

CE mark

Made in Italy

TECHNICAL CARD

Thermal input (Kw) 20,8

net weight (Kg)	198
breadth (mm)	800
depth (mm)	900
height (mm)	900



HIGH POWER



13
kW ▶ 760x750 mm



GN 2/1
530 x 650 mm x 4 pos.

con FIAMMA PILOTA
with PILOT FLAME
avec VEILLEUSE
mit ZUNDFLAMME



MAXIMA 900

high+power

	n.	2
	kW	6,5
	kcal/h	5.590
	Btu/h	22.178
	GN	2/1
	mm	530 x 650 x 4 pos.
	kW	7,8
	kcal/h	6.708
	Btu/h	26.614
TOT.		
	kW	20,8
	kcal/h	17.888
TOT.	Btu/h	70.970
	G30/G31	kg/h 1,64
	G20	m³/h 2,20
	G25	m³/h 2,56
	Kg	198



