



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



| CODE | DESCRIPTION | PRICE/DELIVERY |
|---------------------|--|----------------|
| BS-E9P2M/IND | ELECTRIC COOKER WITH 2 INDUCTION ZONES on OPEN CABINET, BERTOS MAXIMA 900 line, POWER INDUCTION Series, with 2 SQUARE ZONES measuring 270x270 mm, INDEPENDENT CONTROLS, 9 power levels, V.400/3+N, Kw.10.00, Weight 55 Kg, dim.mm.400x900x900h | |

PROFESSIONAL DESCRIPTION

ELECTRIC COOKER with 2 INDUCTION ZONES on OPEN CABINET, MAXIMA 900 Line, POWER INDUCTION Series :

- **worktop and front and side panels** in **AISI 304 stainless steel** ;
- stainless steel interior;
- **6 mm thick glass ceramic top** ;
- **perfectly smooth surface** which guarantees quick cleaning, in just a few gestures and in a few minutes, without the use of aggressive detergents;
- **maximum energy saving** as the heating of the cooking area is activated only when the pan is in direct contact with the surface;
- energy saving is ensured by the **immediate achievement of the maximum temperature** inside the cooking containers whilst keeping the hob completely cold;
- **the high energy efficiency is given by the absence of heat dispersion** and consumption reduced by over 30%;
- **the heating zone self-regulates** based on the diameter of the pan;
- **immediate automatic interruption when the pan is removed from the hob** ;
- **digital indicator** that immediately indicates the **set power level, from 1 to 9** ;
- power regulation via robust high-precision control;
- **square areas measuring 270 x 270 mm and power 5 kW** ;
- **cooking zone power n°x Kw : 2 x 5** ;
- **2 year warranty** .

Accessories/Options :

- right/left door per compartment

CE mark

Made in Italy

TECHNICAL CARD

power supply Trifase

| | |
|------------------------|------------|
| Volts | V 400/3 +N |
| frequency (Hz) | 50 |
| net weight (Kg) | 55 |
| breadth (mm) | 400 |
| depth (mm) | 900 |
| height (mm) | 900 |



MAXIMA 900



| | |
|----|-----------|
| n. | 2 |
| mm | 270 x 270 |
| kW | 5 |



| | |
|-----------------------|--|
| 380-415 V3N~ 50/60 Hz | |
|-----------------------|--|



| | |
|---------|----|
| TOT. kW | 10 |
|---------|----|



| | |
|----|----|
| Kg | 55 |
|----|----|







| |
|----------------|
| 900 35 3/8" |
| 900 35 3/8" |
| 400 15 3/4" |

POWER INDUCTION

| | |
|------|--------------|
| 5 kW | ▶ 270x270 mm |
| 5 kW | |

