

TECNOSERVICE'21 srl by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



- the elegance of the finishes and the design of the structure make the KIBUK refrigerated counter essential both in classic venues and in settings characterized by simple, clean lines;
- with a depth of just 900 mm , it is ideal for placement in narrow environments ;
- curved glass that opens downwards ;
- low energy consumption;
- display tank made without the use of CFCs;
- stainless steel worktop ;
- stainless steel display surface ;
- thermoformed and insulated shoulders (50 mm thick each) with tempered glass side ;
- electronic control panel;
- non-refrigerated reserve at counters;
- ceiling light with neon lighting ;
- ease of installation;
- Manual, removable evaporator-condensate tray.
- 0
- front finish STANDARD RAL COLORS : ZINC YELLOW RAL 1018, RED RAL 3020, BLUE RAL 5013, GREEN RAL 6026, BLACK RAL 9005, MELON YELLOW RAL 1028, ORANGE RAL 2008, PASTEL BLUE RAL 5024, LIGHT GREEN RAL 6019, WHITE RAL 9010;
- color of the SHOULDERS of the standard bench: BLACK, WHITE (to be specified when ordering).

TECHNICAL DATA :

- $\circ~$ Length including shoulders (thickness 50 mm each) 1060 mm
- Power absorbed by lighting (standard equipment) N°/W 1x18
- Display surface 0.6 m²
- Reserve volume in liters 120
- Number of non-refrigerated reserve doors (opening thickness 240x440 mm) n°1

OPTIONAL / ACCESSORIES :

- Front finish in wood-stained MDF-hydro, available colours: WHITE, DARK BROWN, BLACK (to be specified when ordering).
- Intermediate shelf in tempered glass with supports
- Rear sliding plexiglass closures
- Nylon cutting board
- Stainless steel scale support
- Movable glass divider
- Wheel set
- Stainless steel paper holder
- Knife holder
- Packed in a wooden cage (glasses removed).

CE MARK

MADE IN ITALY

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,11	
gross weight (Kg)	125	
breadth (mm)	1060	
depth (mm)	900	
height (mm)	1245	
TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY









