



CODE	DESCRIPTION	PRICE/DELIVERY
<b>TH-MATICMANU8</b>	Semi-automatic cabinet purifier/softener, manual activation of regeneration via button, max flow rate 500 l/h, dim.mm.245x340x485h	<b>€ 221,04</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery from 8 to 15 days</b>

#### PROFESSIONAL DESCRIPTION

##### SEMI-AUTOMATIC SOFTENER CABIN, with MANUAL ACTIVATION of REGENERATION THROUGH A BUTTON :

- **Max flow rate** : 500 LT/H
- **Min Pressure** : 1.5 ATE
- **Max pressure** : 7 ATE
- **Min - max water temperature** : 2 - 35 °C
- **Inlet - Outlet connection** : 3/8 M
- **Drain Fitting** : HOSE HOLDER DIAM.14 MM
- **Regeneration duration** : 22' MINUTES
- **Quantity of salt consumed during Regeneration** : 0.8 KG.
- **Hardness Mixing System** : Yes

**Limestone is mainly responsible for all the problems of blockage and damage to pipes , taps , coils , boilers and a significant increase in energy consumption which is often not noticed. The advantages deriving from the use of softened water are concrete and tangible .**

**The softener mod. MATIC MANU 8 has been designed to meet the needs of those who supply equipment for bars , large kitchens , restaurants , hotels and manufacturers or traders of coffee machines , roasters, ovens and dishwashers .**

The main features of this softener are its **very small size** , its **compactness** , **suitable for installation in minimum spaces** and the **ease of carrying out the regeneration** which, combined with an application that can be downloaded on APPLE and ANDROID, allows the regeneration to be carried out correctly and within the times indicated, without waste of time.

##### IDEAL FOR THE CONNECTION OF :

Ideal for convection ovens

Or:

N.1 Coffee machine 2 groups

**CE MARK**

#### TECHNICAL CARD

breadth (mm) 245

<b>depth (mm)</b>	340
<b>height (mm)</b>	485