

**TECNOSERVICE'21 srl** by Tinti Sergio Via Carlo Pisacane, 134

61032 Fano (PU) Italy

P.IVA IT0200411413

Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



## **TECHNICAL CARD**

 breadth (mm)
 245

 depth (mm)
 340

 height (mm)
 485

## PROFESSIONAL DESCRIPTION

SEMI-AUTOMATIC CABIN WATER SOFTENER, with MANUAL ACTIVATION OF REGENERATION VIA BUTTON :

- Max flow rate : 500 LT/H
- Min Pressure : 1.5 ATE
- Max Pressure : 7 ATE
- Water Temperature min max : 2 35 °C
- Inlet Outlet connection : 3/8 M
- Exhaust Connection : HOSE HOLDER DIAM.14 MM
- Regeneration Duration : 22' MINUTES
- Quantity of salt consumed during regeneration : 0.8 KG.
- Hardness Mixing System : Yes

Limescale is the main cause of all the problems of blockages and damage to pipes , taps , coils , boilers and of a notable increase in energy consumption that we often don't realize. The advantages derived from the use of softened water are concrete and tangible .

The MATIC MANU 8 mod. water softener has been designed to meet the needs of those who supply equipment for bars , large kitchens , restaurants , hotels and manufacturers or traders of coffee machines , roasters, ovens and dishwashers . The main features of this softener are its extremely small size , its compactness , suitable for installation in minimal spaces and the ease of carrying out the regeneration which, combined with an application downloadable on APPLE and ANDROID, allows the regeneration to be carried out correctly and within the indicated times, without wasting time. IDEAL FOR CONNECTING :

Ideal for convection ovens

Or:

N.1 2-group coffee machine **CE MARK** 

DESCRIPTION

## PRICE/DELIVERY

Semi-automatic cabinet purifier/softener, manual activation of regeneration via button, max flow rate 500 l/h, dim.mm.245x340x485h

€ 221,04 VAT escluded Shipping to be calculed

Delivery from 8 to 15 days