



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-BECO-71	Countertop Pastry Sheeter, with BELTS-MATCHES, 71x50 cm, MANUAL CONTROLS, Folding Tables 710 mm long, ROLLING ROLLERS mm. 500, ROLLER OPENING from: 0 to 40 mm, Weight 90 Kg, kw 0.55, dim. open mm. 1480x870x600	€ 3.117,90 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

PASTRY SHEETER with 71x50 cm BELTS (Carpets), Bench Version, Professional, Roller opening from 0 to 40 mm, Upward Folding Tables mm long. 710:

- - **Designed for extremely small spaces** , thanks to the **absence of an undercounter** and the stainless steel extension;
 - Designed and engineered to ensure **extremely easy and functional use**, in full compliance with international safety standards;
 - **Reliable, solid and efficient structure** , it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
 - Shoulders and covers in cast aluminium;
 - Using the **handle to adjust the thickness** ;
 - Possibility of working **any type of pasta** , **up to very thin thicknesses**;
 - Micrometric adjustment of the cylinder descent with aluminum handle;
 -
 - **Hard chrome** plated **rolling cylinders** , **ground and polished**;
 - **cylinder diameter: Ø6cm;**
cylinder opening: from 0 cm to 4 cm;
cylinder width: 50cm;
 -
 - **Movement of the BELTS (belts) via joystick**;
 - **1 speed of the BELTS** (with differentiated speed between the entry belt and the exit belt);
 - **Stainless steel protection grills** with safety microswitch;
 - **Tables that fold upwards** , so as to reduce the overall dimensions when the machine is at rest;
 - **Non-removable table** system;
 - **Working dimensions** : 1480 x 870 x 600h mm;
 - **Dimensions at rest** : 650 x 870 x 730h mm;
 -
 - **Low voltage and dual control electrical system** (manual and pedal);
 - **Accident prevention guards** , connected to the electrical system via limit switches;

Optional:

- Also available with single-phase motor;
- **2-speed motor** , with differentiated speed between the entry belt and the exit belt;

•
CE MARK
Made in Italy

TECHNICAL CARD	
power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	0,55
net weight (Kg)	90
breadth (mm)	1480
depth (mm)	870
height (mm)	600