



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TCF133-SF-B500-71	Professional countertop pastry sheeter with 710x500 mm BELTS-MATCHES equipped with UNDERPLATE for FLOUR and PASTRY COLLECTOR, MM ROLLING ROLLERS. 500 with opening from: 0 to 35 mm, weight 117 kg, 0.75 kW, dim. open mm. 1800x880x650h	€ 3.351,87 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

Professional PASTRY SHEETER with 710x500 mm BELTS-MATS with under-top for collecting FLOUR and collecting sheets, roller opening from 0 to 35 mm, upward folding tables 710 mm long;

- Designed and **engineered to ensure extremely easy and functional use**, in full **compliance with international safety standards**;
- **Reliable, solid and efficient structure**, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries ;
- Shoulders and covers in cast aluminium;
- **Designed for extremely small spaces** ;
- Possibility of working **any type of pasta , up to very thin thicknesses**;
- **Micrometric adjustment** of the cylinder opening with **aluminum handle** ;
- Hard chrome plated **rolling cylinders , ground and polished**;
- **cylinder diameter: Ø 6 cm**;
- **cylinder opening: from 0 to 3.5 cm**;
- **cylinder width: 50 cm**;
-
- **Movement of the BELTS-MATCHES via joystick** ;
- Non-removable table system;
- Tables equipped with **flour collection under-tops and dough catchers** at the bottom of the carpets;
- **1 speed of the BELTS** : (with differentiated speed between the entry belt and the exit belt);
- **Incoming belt speed: 16.50 m/minute;**
Output belt speed: 28.50 m/minute;
-
- **Stainless steel protection grills** with safety microswitch;
- **Tables that fold upwards** , so as to reduce the overall dimensions when the machine is at rest;
- **Working dimensions** : 1800 x 880 x 650h mm;
- **Dimensions at rest** : 600 x 880 x 860h mm;
-
- **Low voltage and dual control electrical system** (manual and pedal);
- **Accident prevention guards** , connected to the electrical system via limit switches;

Optional

- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

CE MARK
Made in Italy

TECHNICAL CARD

power supply	Trifase
Volts	V 400/3
frequency (Hz)	50
motor power capacity (Kw)	0,75
net weight (Kg)	117
breadth (mm)	1800
depth (mm)	880
height (mm)	650