

TECNOSERVICE'21 srl by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



Professional floor-standing PASTRY SH	EETER, with 1400x600 mm	BELTS-MATS, with UNDERC	OUNTER for FLOUR	collection and	
PASTRY COLLECTION, Roller opening from 0 to 35 mm, Foldable and EXTRACTABLE TABLES 1400 mm long:					
······································			••		
_					

- Designed and engineered to ensure extremely easy and functional use , in full compliance with international safety standards;
- Reliable, solid and efficient structure, it meets the needs of restaurants, hotels, pastry shops and small and medium-sized bakeries;
 Shoulders and covers in cast aluminium;
- Shoulders and covers in cast aluminium;
- Possibility of working any type of pasta, up to very thin thicknesses;
- Hard chrome plated rolling cylinders, ground and polished;
- Micrometric adjustment of the cylinder opening with aluminum handle;
- cylinder diameter: Ø7cm;
- cylinder opening: from 0 cm to 3.5 cm;
- cylinder length: 60cm;
- Paste scraper on easily removable cylinders , for easy and effective cleaning;
- 0

0

0

- Movement of the BELTS-MATCHES via pedal control;
- Variable speed conveyor belts-belts to avoid wrinkles in the pastry;
- Stainless steel protection grills with safety microswitch;
- Shielded bearings to avoid flour infiltration;
- Tables that fold upwards, so as to reduce the overall dimensions when the machine is at rest;
- Removable Table System with Stainless Steel Undertop for FLOUR Collection and Pasta Collector;
- Mounted on wheels to facilitate movement;
- 0

• Working dimensions : 3180 x 1010 x 1160h mm;

• Dimensions at rest : 980 x 1010 x 2150h mm;

- 0
- Low voltage and dual control electrical system (manual and pedal);
- Accident prevention guards , connected to the electrical system via limit switches;

Optional:

- Special croissant cutting device;
- Different cutting rollers with particular sizes and shapes on request;
- Also available with single-phase motor;
- 2-speed motor, with differentiated speed between the entry belt and the exit belt;

CE MARK Made in Italy

TECHNICAL CARD				
power supply	Trifase			
Volts	V 400/3			
frequency (Hz)	50			
motor power capacity (Kw)	0,75			
net weight (Kg)	219			
breadth (mm)	3180			
depth (mm)	1010			
height (mm)	1160			