

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE

DESCRIPTION

PRICE/DELIVERY

LH-ICOOL40W

Refrigerated wine cellar, 1 glass door, capacity 126
bottles temporature ±4°C/±18°C | ±16°C/±10°C/±5°C

€ 713,02

Refrigerated wine cellar, 1 glass door, capacity 126 bottles, temperature $+4^{\circ}\text{C}/+18^{\circ}\text{C} \mid +16^{\circ}\text{C}/+10^{\circ}\text{C}/+5^{\circ}\text{C}$, static refrigeration with fan, LED lighting, V.230/1, Kw.0,23, Weight 67 Kg, dim.mm.600x650x1850h

VAT escluded
Shipping to be calculed

Delivery from 4 to 9 days

PROFESSIONAL DESCRIPTION

REFRIGERATED WINE CELLAR, 1 glass door, capacity 126 bottles of 0.75 lt :: • External surface in pre-painted sheet metal with anti-corrosion treatment; Inner surface in ABS; • Frameless infinity door; • Static refrigeration with on/off fan; $^{\circ}$ Temperature: +16 °C /+10 °C /+5 °C fan OFF | +4 °C / +18 °C fan ON ; o Climatic Class: 4; • R600A refrigerant; Energy consumption KwH/24H: 2.84; o Net-gross volume: Lt. 342 / 382; • Capacity 126 bottles of 0.75 I (indicative and variable data according to the different packaging); • Electronic thermostat; • Insulation thickness 40 mm; $\,\circ\,$ Automatic defrosting when the compressor is off + Manual ; \circ Lighting: 2 vertical LEDs; o Automatic door lock; Key and lock; Door reversibility; Shelves: N° 5 - mm 513x410; o 2 Feet, 2 Wheels.

Accessories/Options:

- Wooden shelves
- 。 Sub Zero (Temp. -2°C/+2°C) / Digital Thermometer Electronic Regulator

CF mark

CE mark		
TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,23	
net weight (Kg)	67	
gross weight (Kg)	79	
breadth (mm)	600	
depth (mm)	650	
height (mm)	1850	









Mensole in legno - Optional Wooden shelves - Optional





Dimensioni mm / Dimensions mm

Modello / Model	CLW 372 VG	ICOOL 40 W
Dimensioni Esterne (LxPxH) External Dimensions (WxDxH)	600 x 624 x 1863	600 x 650 x 1850
Dimensioni Imballo (LxPxH) Packaging Dimensions (WxDxH)	660 x 710 x 1990	660 x 710 x 1990

Dimensioni Interne mm / Inner Dime	ensions mm	37/1/1/1/
A - Larghezza / Width	522	522
B - Profondità / Depth	449	449
C - Altezza / Height	1557	1557
D - Profondità Min. / Min. Depth	179	179
E - Altezza Min. / Min. Height	1337	1337

Dimensioni Personalizzazione (LxH) mm / Sticker	Dimensions (WxH) mm
Vetro / Glass	503 x 1544	503 x 1544

TEMERATURA VENTOA OFF - FAN OFF TEMERATURE TEMERATURA VENTOA ON - FAN ON TEMERATURE TEMERATURA VENTOA ON - FAN ON TEMERATURE

Capienza / Capacity

Modello / Model	CLW 372 VG	ICOOL 40 W
Btg cl. 75 / Btl cl. 75	126	126

Dati indicativi e variabili a seconda dei diversi packaging Variable data depending on the different packaging