



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



| CODE | DESCRIPTION | PRICE/DELIVERY |
|--------------------------|---|---|
| FC-M-GN1410BTG-FC | Professional Freezer-Freezer Cabinet, 2 Glass Doors, with Monobloc, Plug-in System, Ventilated, 1300 lt, Temp.-18°/-22°C, GN 2/1, Ecological in Class E, Gas R290, V. 230/1, Kw.0,815, Weight 206 Kg, dim.mm.1480x830x2010h | € 1.695,08 <i>VAT excluded</i> Shipping to be calculated Delivery from 8 to 15 days |
| PROFESSIONAL DESCRIPTION | | |

FREEZER-FREEZER CABINET 2 GLASS DOORS , Professional Line, It.1300, Ventilated, GN 2/1, Temp.-18°/-22°C, with monobloc, plug-in system, Class E :

- **made of AISI 201 stainless steel ;**
- **ventilated refrigeration ;**
- **Monobloc refrigeration unit ;**
- **refrigeration unit with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- silent motor;
- **monobloc protected by stainless steel sheet ;**
- **temperature -18°/-22°C ;**
- **electronic temperature control with digital thermostat ;**
- **energy class C ;**
- **ecological refrigerant gas R290 ;**
- maximum ambient temperature: +32°C;
- maximum ambient humidity: 60%HR;
- electric resistance around the door frame to eliminate condensation;
- **insulation thickness 60 mm ;**
- **automatic defrost ;**
- **electronic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- door with return spring and reversible;
- door lock with key;
- door seal removable without tools;
- internal LED light;
- bottom with rounded corners;
- external bottom and back panels in galvanized sheet metal;
- Height-adjustable feet.

Supplied :

- 6 GN 2/1 grills
- 6 pairs of guides

CE MARK

TECHNICAL CARD

| | |
|----------------------------------|----------|
| power supply | Monofase |
| Volts | V 230/1 |
| frequency (Hz) | 50 |
| motor power capacity (Kw) | 0,815 |
| net weight (Kg) | 206 |
| gross weight (Kg) | 227 |
| breadth (mm) | 1480 |
| depth (mm) | 830 |
| height (mm) | 2010 |



ENERGY



FORCOLD

M-GN1410BTG-FC



7541 kWh/annum



1.45 m²



-12°C

-15°C

8102/2010