



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TCF375-000100	1 Door Professional Refrigerator Cabinet, capacity 700 liters, Ventilated, temp. -2 ° / + 8 ° C, Ecological version with ENERGY SAVING, CLASS A - Stainless steel 304, V.230 / 1, Kw.0.43, dim. mm.740x815x2085h.	

PROFESSIONAL DESCRIPTION

1 door REFRIGERATOR, ENERGY SAVING ECOLOGICAL version - CLASS A, HIGH THICKNESS cabinet, capacity 700 liters, operating temperature -2 ° + 8 ° C:

- **exterior / interior** in **AISI 304** stainless steel,
- **ventilated refrigeration** ,
- **insulation thickness 75 mm** ,
- rounded internal corners,
- adjustable feet in stainless steel,
- **reversible door** with 105 ° stop,
- **door handle Profiled at full height in PV C** ,
- replaceable magnetic gasket,
- **3 pairs of stainless steel guides** and **3 GN2 / 1 rilsan grids** per door,
- **evaporator treated by cataphoresis** ,
- **pvc evaporator cover** ,
- totally replaceable refrigerant system, running on ecological **R290 Natural gas** , which ensures an **Energy Saving that reaches peaks of 80%** compared to similar products ... few Virtuosos.
- automatic defrost,
- automatic condensation evaporation,
- **Electronic thermometer-thermostat** with display,
- **door lock** with key,

Electronic control unit with :

- keyboard protection flap,
- high temperature alarm,
- door open alarm,
- maximum temperature storage.

Accessories / Optionals :

- Interior lighting
- Kit of 4 swiveling wheels (2 with brake), diameter 128 mm
- Door Opening Kit with Pedal

CE mark

Made in Italy


TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,43
net weight (Kg)	125
gross weight (Kg)	150
breadth (mm)	740
depth (mm)	815
height (mm)	2085

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
---------------	-------------	----------------


TCF375-000504



Couple of type C guides

Pair of guides type C 605 mm for 2/1 GN grids (650x530 mm)


TCF375-000506



GN 2/1 plastic coated grid


GN 2/1 plasticized grid (mm 650x530)

TCF375-000503



Led lighting
1 door led lighting

TCF375-000505




GN2 / 1 stainless steel grid
GN 2/1 stainless steel grid (650x530 mm)

TCF375-000501



Door opening kit with pedal
Door opening kit with pedal

TCF375-000502



Kit of 4 pivoting stainless steel wheels with brake
Kit of 4 pivoting stainless steel wheels with brake, h 128 mm.



Caratteristiche principali



Fondo modulare
Consente l'installazione su ruote, piedini, zoccolo fisso o mobile.



Isolamento 75 mm
Spessore isolamento 75 mm CFC/HCFC free.



Serratura e fermo porta
Porte autochiudenti reversibili con fermo a 105° dotate di serratura con chiave.



Guarnizioni sostituibili ad alta tenuta
Geometria a tripla camera con innovativa miscela D7, efficacia d'isolamento superiore del 35% rispetto alle tradizionali.



Apertura a pedale
Facilita la movimentazione e l'inserimento di teglie e bacinelle pesanti (optional).



Evaporazione a costo zero
L'acqua prodotta dagli sbrinatori evapora sfruttando il calore dissipato dal sistema refrigerante.



Ventilatore intelligente
I ventilatori si arrestano automaticamente all'apertura della porta per evitare l'aspirazione di aria calda.



Guide e cremagliere
Guide e cremagliere inox smontabili senza ausilio di attrezzi.



Armadio 700 lt

