



CODE	DESCRIPTION	PRICE/DELIVERY
TP-KB81-R	DISPLAY HOT DISPLAY, counter-top, 1-STAGE, STAINLESS STEEL, glass on 4 sides, Plexiglas drop-side doors operator side, complete with HUMIDIFIER, temperature from + 30 ° to + 90 ° C, suitable for GN 1/1 + 1 pans / 2, V.230 / 1, Kw.1.00, dim.mm.870X370X240h	€ 428,53 VAT excluded Shipping to be calculated Delivery from 4 to 9 days

PROFESSIONAL DESCRIPTION

DISPLAY HOT DISPLAY, counter-top, 1-STAGE in STAINLESS STEEL, suitable for GASTRO-NORM 1/1 + 1/2 containers:

- **furnishing object** able to **enhance the exposed product and the environment** in which it is installed;
- **structure** in **stainless steel sheet**, with scotch brite brushed finish;
- **glass on all 4 sides** for displaying baked pastry products, croissants, muffins, etc.;
- the **useful space** in height **for the shelves is 15 cm**;
- plexiglass **drop doors on the operator's side**;
- **1 stainless steel top**;
- **heating obtained** with a **high efficiency radiant resistance** housed in a special container, controlled by a **thermostat adjustable from + 30 ° to + 90 ° C** and an indicator lamp;
- a water drawer in stainless steel allows **the humidification of the products**;
- base frame is supplied with a removable tray, suitable for housing **Gastro-Norm 1/1 + 1/2 bowls**;
- uprights with rounded square section and, together with the upper frame, give the structure an **exceptional sturdiness**;
- **sides and front** are in 4 mm thick **tempered glass**;
- the **upper surface** is in 5 mm thick **tempered glass**, fixed to the structure with 4 sturdy wide-head screws;
- the hinges applied with a pressure screw allow the **almost total opening of the door (170 °)**;
- on-off light switch, plug-in cable with plug;
- adjustable feet for perfect leveling.

ACCESSORIES / OPTIONAL:

- On request fall doors on the 2 fronts (self-service use).
- On request intermediate glass shelves.

CE marking
Made in Italy

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	1
net weight (Kg)	17
breadth (mm)	870

depth (mm)	370
height (mm)	240