



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>EM-SYSTEM35</b>	EUROMATIC BELL VACUUM PACKAGING MACHINE for counter, SYSTEM Line, CHAMBER mm. 360x400x190h, 350 mm WELDING BAR. VACUUM PUMP 12 / 14.4 meters / cubic / hour, V.230 / 1, Kw. 0,45, Weight Kg. 50, external dimensions mm. 460x500x420h	<b>€ 1.546,49</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days
PROFESSIONAL DESCRIPTION		

## COUNTER BELL VACUUM PACKAGING MACHINE, SYSTEM Line with DIGITAL CONTROLS :

- **New series** of digital counter top packaging machines;
- Equipped with **brand new electronic card** ;
- **Digital control** panel with 3 editable and customizable programs;
- **1 program for marinating meat** ;
- **350 mm sealing bar** with completely renewable wiring;
- Pump self- **cleaning / heating system** for optimal management of the packaging machine, reducing maintenance times and costs;
- **GASTROVAC function** for creating external vacuum in GN containers;
- **EXTRAVAC function** , which offers **a second vacuum phase lasting 5 seconds** (particularly suitable for minced and boned meat);
- Quick stop / welding;
- Carter with 90 ° opening to facilitate access to the inside of the packaging machine;
- **Vacuum chamber 360x400x190h mm**, made of stainless steel molded in a single piece with rounded corners for maximum hygiene and easy cleaning;
- **12 / 14.4 meters / cubic / hour vacuum pump**;
- **Simple and immediate electronics** , 18-level sealing for any type of bag;

◦ **Note** : Possibility of **external vacuum** with **the use of embossed envelopes** , (as shown in the photo).

### OPTIONAL / ACCESSORIES :



- Possibility of **vacuuming in external containers** or **gastro-norm basins** using a special kit - Code EMATUBOGN.
- Predisposition for **inert gas kit** - Code EMGASINERTE.
- Sealing **bar with piston lifting** - Code EMBSP.
- Sealing **bar with envelope excess cut (scrap)** - Cod. EMTS.
- Bell stop bar - Code EMBF.
- Inclined plane for liquid packaging - Code EMPI.
- Machine support trolley - Code EMCR.

**CE mark**  
**Made in Italy**

#### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	5060
<b>motor power capacity (Kw)</b>	0,45
<b>net weight (Kg)</b>	50
<b>breadth (mm)</b>	460
<b>depth (mm)</b>	500
<b>height (mm)</b>	450

#### TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>EM-BF</b> 	<b>TECHNOCHEF - Bell holder, Mod.BF</b> Bell stop bar	<b>€ 24,99</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days
<b>EM-BSPVE</b> 	<b>Sealing bar with piston</b> Piston lifting sealing bar	<b>€ 79,61</b> <i>VAT excluded</i> <b>Shipping to be calculated</b> <b>Delivery</b> from 4 to 9 days

**EM-PI****Inclined plane, Mod.PI**

Inclined surface for liquid packaging, suitable for bell-shaped packaging machines

**€ 85,74**

*VAT excluded*  
Shipping to be calculated

**Delivery** from 4 to 9 days

**EM-TUBOGN****Tube with adapter sleeve in gastro containers**

Tube with adapter sleeve in gastro containers

**€ 102,01**

*VAT excluded*  
Shipping to be calculated

**Delivery**

**EM-GSR****Gas inert, Mod.GSR**

Inert gas kit for chamber vacuum machines

**€ 242,57**

*VAT excluded*  
Shipping to be calculated

**Delivery** from 4 to 9 days

**EM-CR****Machine Support Trolley, Mod.CR**

Support trolley

**€ 282,20**

*VAT excluded*  
Shipping to be calculated


**Delivery** from 4 to 9 days




**STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA**  
STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello digitale  
Digital panel



Sistema autopulizia olio  
Oil made auto cleaning system



Pannello comandi a totale tenuta  
contro umidità  
Waterproof control Panel



Carter apribile a 90°  
90° openable carter



Barre saldanti estraibili  
Removable sealing bars



Vasca inox con angoli stondati  
senza saldature  
Entirely printed stainless steel  
vacuum chamber, with internal  
round corners



Connessione per attacco gastrovac  
Connection for the gastrovac system



Set tavole di riempimento in  
polietilene  
Polyethylene filling squares set



## OPTIONAL PER CONFEZIONATRICI A CAMPANA OPTIONALS ONLY FOR CHAMBER MACHINES



Installazione gas inerte  
Arrangement for idle gas



Vasca doppia altezza per  
confezionamento liquidi (SYSTEM 40)  
Special double height vacuum chamber  
to pack liquids (SYSTEM 40)



Pompa Bosch  
Bosch Pump



Saldatura con pistoni senza cavi  
Sealing with cableless pistons



Tensione e frequenza speciale  
Voltage and special frequency



Carrello supporto macchina  
Chariot on wheels



Taglio Eccedenza  
Exceeding cutting bar



Sistema bloccaggio campana  
Lid Hook



Piano inclinato per liquidi  
Inclined plane for liquids



Modifica parametri vuoto / saldatura / tempo immissione gas  
- Attivazione / Disattivazione GAS INERTE  
used to modify vacuum/sealing/gas injection time parameters  
- connection/disconnection of inert gas

Funzione Gas Inerte  
Attivata (LED ACCESO)  
Inert gas function on  
(LED on)

1. Settaggio % di vuoto
  2. Settaggio tempo di saldatura
  3. Attivazione funzione saldatura rapida
  4. Attivazione funzione VAC STOP:  
interruzione anticipata del ciclo di vuoto
1. Setting of the vacuum percentage  
2. Setting of the sealing time  
3. Activation of RAPID SEALING: if you push the button once  
4. Activation of VAC STOP FUNCTION (stop in advance the vacuum cycle) if you push the button twice



Accensione / Spegnimento  
confezionatrice  
switch on / switch off of the  
vacuum packaging machine

Funzione di vuoto in  
continuo, per aspirazione  
in contenitori gastro  
nanstop vacuum function: done  
with suction in gastro bowls

Definizione della percentuale di  
vuoto raggiunta in camera  
vacuum level reached in the  
chamber

Funzione di pulizia olio pompa del  
vuoto.  
Premendo il tasto per tre secondi  
a campana chiusa  
pushing the button for three  
seconds (only when the bell is  
closed) the cleaning function of  
the vacuum pump begins

Definizione tempo di saldatura  
(espresso in secondi)  
sealing time (in seconds)