



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
EM-SYSTEM45	EUROMATIC BELL VACUUM PACKAGING MACHINE for counter, SYSTEM Line, CHAMBER mm. 460x500x220h, WELDING BAR of 450 mm, VACUUM PUMP of 20/24 meters / cubic / hour, V.230 / 1, Kw 0.90, Weight Kg. 68, external dimensions mm. 560x610x450h	€ 2.128,91 <i>VAT excluded</i> Shipping to be calculated Delivery from 4 to 9 days
PROFESSIONAL DESCRIPTION		

COUNTER BELL VACUUM PACKAGING MACHINE, ECOVAC Line :

- **New series** of digital counter top packaging machines;
- Equipped with **brand new electronic card** ;
- **Digital control panel with 3** editable and customizable programs;
- **1 program for marinating meat** ;
- **450 mm sealing bar** with completely renewable wiring;
- **Pump self-cleaning / heating system** for optimal management of the packaging machine, reducing maintenance times and costs;
- **GASTROVAC function** for creating external vacuum in GN containers;
- **EXTRAVAC function** , which offers a **second vacuum phase lasting 5 seconds** (particularly suitable for minced and boned meat);
- Quick stop / welding;
- Carter with 90 ° opening to facilitate access to the inside of the packaging machine;
- **Vacuum chamber 460x500x220h mm** , made of stainless steel molded in a single piece with rounded corners for maximum hygiene and ease of cleaning;
- **20/24 meters / cubic / hour vacuum pump** ;
- **Simple and immediate electronics** , 18-level sealing for any type of bag;
- **Note** : Possibility of **external vacuum** with **the use of embossed envelopes** , (as shown in the photo).

OPTIONAL / ACCESSORIES:

- Possibility of **vacuuming in external containers** or **gastro-norm basins** using a special kit - Code EMATUBOGN.
- Predisposition for **inert gas kit** - Code EMGASINERTE.
- Sealing **bar with piston lifting** - Code EMBSP.
- Sealing **bar with envelope excess cut (scrap)** - Cod. EMTS.
- Bell stop bar - Code EMBF.
- Inclined plane for liquid packaging - Code EMPI.
- Machine support trolley - Code EMCR.

CE mark

Made in Italy

TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	5060
motor power capacity (Kw)	0,9
net weight (Kg)	68
breadth (mm)	560
depth (mm)	610
height (mm)	450

TECHNICAL CARD

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
---------------	-------------	----------------

EM-BF



TECHNOCHEF - Bell holder, Mod.BF
Bell stop bar

€ 24,99

VAT excluded

Shipping to be calculated

Delivery from 4 to 9 days

EM-BSPVE



Sealing bar with piston
Piston lifting sealing bar

€ 79,61

VAT excluded

Shipping to be calculated

Delivery from 4 to 9 days

EM-PI**Inclined plane, Mod.PI**

Inclined surface for liquid packaging, suitable for bell-shaped packaging machines

€ 85,74

VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days**EM-TUBOGN****Tube with adapter sleeve in gastro containers**

Tube with adapter sleeve in gastro containers

€ 102,01

VAT excluded
Shipping to be calculated

Delivery**EM-GASINERTEURANO****TECHNOCHEF - Inert gas, Mod. GASINERTE**

Inert gas kit for vacuum chamber machines

€ 288,20

VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days**EM-CR****Machine Support Trolley, Mod.CR**

Support trolley

€ 282,20


VAT excluded
Shipping to be calculated

Delivery from 4 to 9 days**STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA**


STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello digitale
Digital panel



Sistema autopulizia olio
Oil made auto cleaning system



Pannello comandi a totale tenuta
contro umidità
Waterproof control Panel



Carter apribile a 90°
90° openable carter




Barre saldanti estraibili
Removable sealing bars



Vasca inox con angoli stondati
senza saldature
Entirely printed stainless steel
vacuum chamber, with internal
round corners



Connessione per attacco gastrovac
Connection for the gastrovac system



Set tavole di riempimento in
polietilene
Polyethylene filling squares set



OPTIONAL PER CONFEZIONATRICI A CAMPANA

OPTIONALS ONLY FOR CHAMBER MACHINES



Installazione gas inerte
Arrangement for idle gas



Vasca doppia altezza per
confezionamento liquidi (SYSTEM 40)
Special double height vacuum chamber
to pack liquids (SYSTEM 40)



Pompa Bosch
Bosch Pump



Saldatura con pistoni senza cavi
Sealing with cableless pistons



Tensione e frequenza speciale
Voltage and special frequency



Carrello supporto macchina
Chariot on wheels



Taglio Eccedenza
Exceeding cutting bar



Sistema bloccaggio campana
Lif Hook



Piano inclinato per liquidi
Inclined plane for liquids



Modifica parametri vuoto / saldatura / tempo immissione gas
- Attivazione / Disattivazione GAS INERTE
used to modify vacuum/sealing/gas injection time parameters
- connection/disconnection of inert gas

Funzione Gas Inerte
Attivata (LED ACCESO)
Inert gas function on
(LED on)

1. Settaggio % di vuoto
 2. Settaggio tempo di saldatura
 3. Attivazione funzione saldatura rapida
 4. Attivazione funzione VAC STOP:
interruzione anticipata del ciclo di vuoto
- 1. Setting of the vacuum percentage*
2. Setting of the sealing time
3. Activation of RAPID SEALING: if you push the button once
4. Activation of VAC STOP FUNCTION (stop in advance the vacuum cycle) if you push the button twice



Accensione / Spegnimento
confezionatrice
switch on / switch off of the vacuum packaging machine

Funzione di vuoto in
continuo, per aspirazione
in contenitori gastro
nanstop vacuum function done with suction in gastro bowls

Definizione della percentuale di
vuoto raggiunta in camera
vacuum level reached in the chamber

Funzione di pulizia olio pompa del
vuoto.
Premendo il tasto per tre secondi
a campana chiusa
pushing the button for three seconds (only when the bell is closed) the cleaning function of the vacuum pump begins

Definizione tempo di saldatura
(espresso in secondi)
sealing time (in seconds)