

#### TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA IT0200411413

Tel +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
TV EVT422	Pasa holder for 420 stainless steel evens with lower	

Base holder for 430 stainless steel ovens with lower shelves for Mod: TK-EKF423; TK-EKF443; TK-EKF523, Weight Kg.23,2, dim.mm.610x630x791h

**Delivery** from 4 to 9 days

### PROFESSIONAL DESCRIPTION

## **TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
CODE/FICTORES	DESCRIPTION	FRICE/DELIVER

## TK-EKF423NU



#### **TECNOEKA - ELECTRIC VENTILATED CONVECTION** OVEN with HUMIDIFIER, 4 trays 429x345 mm, Professional, mod. EKF423NU

VENTILATED ELECTRIC CONVECTION OVEN with HUMIDIFIER, cooking chamber for 4 TRAYS measuring 429x345 mm, ELECTROMECHANICAL CONTROLS, V.230/1, Kw.3.1, Weight 36.4 Kg, external dimensions mm.590x709x589h

## Delivery from 4 to 9 days

Delivery from 4 to 9 days

## TK-EKF423NM



TK-EKF423NUD

#### **TECNOEKA - MULTIFUNCTION ELECTRIC** CONVECTION OVEN, 4 trays 429x345 mm, Professional mod.EKF423NM

MULTIFUNCTION ELECTRIC CONVECTION OVEN, cooking chamber for 4 TRAYS measuring 429x345 mm, ELECTROMECHANICAL CONTROLS, V.230/1, Kw.2.6, Weight Kg.36.4, external dimensions mm.590x709x589h

# **TECNOEKA - VENTILATED ELECTRIC CONVECTION**



OVEN with DIRECT STEAM, for 4 trays 429x345 mm, mod. EKF423NUD

VENTILATED ELECTRIC CONVECTION OVEN with DIRECT STEAM, cooking chamber for 4 TRAYS measuring 429x345 mm, ELECTROMECHANICAL CONTROLS, V.230/1, Kw.3.15, Weight 38 Kg, external dimensions mm.590x709x589h

**Delivery** from 4 to 9 days

TK-EKF523NUD

Delivery from 8 to 15 days



Tecnoeka - Electric STEAM CONVECTION OVEN for 5 GN 2/3 trays (354x325 mm), mod. EKF523NUD CONVENTIONAL STEAM OVEN Electric Ventilated, Professional with cooking chamber for 5 GASTRO-NORM 2/3 TRAYS (mm.354x325) ELECTROMECHANICAL CONTROLS, V.230/1, Kw.3.2, Weight Kg.40, external dimensions mm.550x754x662h