



TECHNICAL CARD

power supply	Monofase
Volts	V 230/1
frequency (Hz)	50
motor power capacity (Kw)	0,32
breadth (mm)	800
depth (mm)	680
height (mm)	1200

PROFESSIONAL DESCRIPTION

REFRIGERATED DISPLAY TROLLEY in WOOD with PLEXIGLASS DOME, capacity 2 GASTRO-NORM 1/1 CONTAINERS, temperature +4°/+10°C:

- **legs in AISI 304 stainless steel tubular** , brushed finish ;
- **plywood panels;**
- **AISI 304 stainless steel tank**, 19 cm high, for GN containers up to 15 cm high ;
- **capacity 2 Gastro-Norm 1/1 containers** (not included);
- **hole in the bottom of the tank for draining condensation** (with tap on request, mandatory for fish);
- semi-cylindrical **plexiglass dome** with opening on 2 sides ;
- control panel with digital thermostat-thermometer and power switch with indicator light ;
- operating temperature: +4°/+10°C ;
- **static refrigeration;**
- 4 swivel wheels with a diameter of 125 mm, 2 of which have brakes ;
- **available in different colours: OAK, WENGE', BLACK, MATT LACQUERED in RAL COLOURS.**

Operating Environmental Conditions:

- Max Ambient Temperature 26°C
- Relative Humidity 60%

Optional/Accessories:

- Drain tap
- Bathtub lighting

CE mark

Made in ITALY

AVAILABLE MODELS

MC-6930/2R



Refrigerated display trolleys

Delivery from 8 to 15 days

MC-6930/2W



Refrigerated display trolleys

Delivery from 8 to 15 days

MC-6930/2RAL



Refrigerated display trolleys

Delivery from 8 to 15 days

TECHNICAL CARD

CODE/PICTURES

MC-A156



DESCRIPTION

Refrigerated display cabinets

PRICE/DELIVERY

Delivery from 3 to 6 days

MC-LED



Refrigerated display cabinets

Delivery from 3 to 6 days

