

TECNOSERVICE'21 srl

by Tinti Sergio Via Carlo Pisacane, 134 61032 Fano (PU) Italy P.IVA ITO200411413 Tel. +39 0721 805911 FAX +39 0721 809794 e-mail: staff@technochef.it www.technochef.it www.technochef.eu

Services and Technologies for professional catering since 1973



PROFESSIONAL DESCRIPTION

Mod.OS-TAG98 - ELECTRIC STRIPS CUTTER with 22 BLADES, for an 8 mm CUT:

- made of anodized aluminum;
- stainless steel blade group;
- $\circ\,$ equipped with 22 blades with distance between each blade of 8 mm;
- $\circ\,$ s maximum thickness of the product to be introduced 20 mm ;
- product feed speed 20 mm per second;
- $\circ~$ blade cover combs to accompany the cutting of the meat;
- $\circ~$ this machine can also be used to ${\mbox{\bf cut}}~\mbox{\bf ham, cheese, vegetables, etc.}$ into ${\mbox{\bf strips}}$;
- $\circ~$ fully hermetic motor with forced air flow cooling system ;
- o reduction gear in oil bath;
- possibility of working for several consecutive hours without heating up the cutting unit and without making any noise;
- the powerful gearmotor unit remains stable on the workbench and does not require any attention;
- available in **SINGLE-PHASE** or **THREE-PHASE** version.

CE mark Made in Italy

TECHNICAL CARD	
net weight (Kg)	23
breadth (mm)	200
depth (mm)	450
height (mm)	440

AVAILABLE MODELS





Delivery from 4 to 9 days

BERKEL - Technochef, Meat cutter in 8 mm strips ELECTRIC STRIPS CUTTER with 22 blades, for a 8 mm cut, V.230/1, Kw.0,4, Weight 23 Kg, dim.mm.200x450x440h

Delivery from 4 to 9 days





BERKEL - Technochef - Meat cutter in 8 mm strips ELECTRIC STRIPS CUTTER with 22 blades, for a 8 mm cut, V.400/3, Kw.0,5, Weight 23 Kg, dim.mm.200x450x440h

TECHNICAL CARD

CODE/PICTURES DESCRIPTION PRICE/DELIVERY

OS-OPT94



Delivery from 4 to 9 days

Rotation reverse two-hand control

Rotation reverse two-hand control

OS-OPT68



Aluminum blade cover Aluminum blade cover

Delivery from 4 to 9 days

OS-OPT84



Delivery from 4 to 9 days

--- Meat tenderizing blade group Meat tenderizer blade unit applicable on TAG strip cutter

