



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>EM-SPRINT</b>	BELL VACUUM PACKAGING MACHINE mod.SPRINT, PLUTONE LINE, with mm. CHAMBER. 410x450x220h, 400 mm SEALING BAR, DIGITAL CONTROLS, V. 230/1 - Kw 1.15 - external dimensions mm. 470x550x400h	<b>Delivery</b> from 4 to 9 days

**PROFESSIONAL DESCRIPTION**

**BENCH COUNTER VACUUM PACKAGING MACHINE PLUTONE Line, Mod.SPRINT, CE standards:**

- **VACUUM CHAMBER 410x450x220h mm** , made of **stainless steel** molded in a **single piece** with **rounded corners** for **maximum hygiene** and **ease of cleaning** ;
- **400 mm WELDING BAR** , with completely removable wiring;
- **Single-program DIGITAL CONTROL** panel with manually activated **timed vacuum percentage** ,
- **VACUUM PUMP of 16 metres / cubic meters / hour** ,
- Internal **vacuum chamber filling platforms** as standard;
- Transparent tank lid with **automatic piston lifting at the end of the work cycle** ;
- **1 work program that can be modified and stored** thanks to the control panel;
- **Pump self-cleaning system** for removing water and humidity;
- Optimal times and reduced maintenance costs;
- **GASTROVAC function** for creating **external vacuum** in GN containers;
- **EXTRAVAC function** which offers a second **vacuum phase of 5 seconds** (suitable for minced and boned meat);
- **Emergency button** for blocking the appliance + rapid welding;
- Carter with 90° opening to facilitate access to the inside of the packaging machine;
- Adjustable zips;
- 
- **Note** : Possibility of **external vacuum** with **the use of embossed envelopes** , (as visible in the photo).

**OPTIONS/ACCESSORIES**



- Possibility of **vacuuming in external containers** or **gastro-norm containers** using a specific kit (Code EM-TUBOGN)
- **Inclined surface** for **packaging liquid products** (Code EM-PI)
- Cart for machine support (EM-CR)

**CE mark**  
**Made in Italy**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	1,15
<b>net weight (Kg)</b>	45
<b>gross weight (Kg)</b>	49
<b>breadth (mm)</b>	470
<b>depth (mm)</b>	550
<b>height (mm)</b>	400

**TECHNICAL CARD**

CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>EM-PI</b> 	<b>Inclined plane, Mod.PI</b> Inclined surface for liquid packaging, suitable for bell-shaped packaging machines	<b>Delivery</b> from 4 to 9 days
<b>EM-TUBOGN</b> 	<b>Tube with adapter sleeve in gastro containers</b> Tube with adapter sleeve in gastro containers	<b>Delivery</b>

## EM-CR



**Machine Support Trolley, Mod.CR**  
Support trolley

Delivery from 4 to 9 days




### STANDARD FUNCTIONS PER CONFEZIONATRICI A CAMPANA


STANDARD FUNCTION ONLY FOR CHAMBER MACHINES



Pannello digitale  
Digital panel



Sistema autopulizia olio  
Oil made auto cleaning system



Pannello comandi a totale tenuta  
contro umidità  
Waterproof control Panel



Carter apribile a 90°  
90° openable carter



Barre saldanti estraibili  
Removable sealing bars



Vasca inox con angoli stondati  
senza saldature  
Entirely printed stainless steel  
vacuum chamber, with internal  
round corners



Connessione per attacco gastrovac  
Connection for the gastrovac system



Set tavole di riempimento in  
polietilene  
Polyethylene filling squares set




### OPTIONAL PER CONFEZIONATRICI A CAMPANA

OPTIONALS ONLY FOR CHAMBER MACHINES



Pompa Busch  
Busch Pump



Carrello supporto macchina  
Charriot on wheels



Piano inclinato per liquidi  
Inclined plane for liquids



Tensione e frequenza speciale  
Voltage and speciale frequency

Modifica parametri vuoto / saldatura  
used to modify vacuum/sealing

Funzione Gas Inerte  
Attivata (LED ACCESSO)  
Inert gas function on  
(LED on)

1. Settaggio % di vuoto
2. Settaggio tempo di saldatura
3. Attivazione funzione saldatura rapida
4. Attivazione funzione VAC STOP:  
interruzione anticipata del ciclo di vuoto

1. Setting of the vacuum percentage
2. Setting of the sealing time
3. Activation of RAPID SEALING. If you push the button once
4. Activation of VAC STOP FUNCTION (stop in advance the vacuum cycle) if you push the button twice



Accensione / Spegnimento  
confezionatrice  
switch on / switch off of the  
vacuum packaging machine

Funzione di vuoto in  
continuo, per aspirazione  
in contenitori gastro  
nonstop vacuum function: done  
with suction in gastro bowls

Definizione della percentuale  
di vuoto raggiunta in camera  
vacuum level reached in the  
chamber

Funzione di pulizia olio pompa  
del vuoto.  
Premendo il tasto per tre secon-  
di a campana chiusa  
pushing the button for three  
seconds (only when the bell is  
closed) the cleaning function of  
the vacuum pump begins

Definizione tempo di saldatura  
(espresso in secondi)  
sealing time (in seconds)