



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



#### TECHNICAL CARD

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,235
<b>net weight (Kg)</b>	233
<b>breadth (mm)</b>	1510
<b>depth (mm)</b>	800
<b>height (mm)</b>	1000

#### PROFESSIONAL DESCRIPTION

**2-DOOR PIZZA COUNTER, with GRANITE WORKTOP and BACKREST, operating temperature -2°/+8°C, CLASS C, FORCOLD brand :**

- **AISI 201 stainless steel structure ;**
- granite worktop on 3 sides;
- **2 refrigerated compartments** capable of holding **600x400x70h mm loaf trays ;**
- operating temperature -2°/+8°C;
- **capacity 390 lt ;**
- **ventilated refrigeration ;**
- **ECOLOGICAL gas R600a ;**
- **Energy CLASS C ;**
- **built-in removable group** for easy maintenance;
- front panel opens with key;
- **circular flow of cold air** so as not to directly touch the product;
- **electronic temperature control with digital thermostat ;**
- electrical resistance around the door frame to eliminate condensation;
- **automatic defrosting** with electric resistance and automatic control of the defrosting temperature;
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- insulation thickness: 60 mm;
- Max. operating temp. / Ambient humidity °C/rh +35/50%




- door with return spring;
- tool-free removable door seal;
- bottom with rounded corners;
- **height-adjustable stainless steel feet** ;
- possibility of leaning against the wall.

**Included :**

- 7 pairs of door guides (no grille supplied)

**CE mark**

CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-PZ2600TN-FC</b>	REFRIGERATED PIZZA COUNTER with 2 DOORS, GRANITE top, temperature -2°/+8°C, Ventilated, ECOLOGICAL R600a gas in Class C, V 230/1, Kw 0.235, Weight 233 Kg, dim.mm.1510x800x1000h.	<b>Delivery</b> from 25 to 35 days

TECHNICAL CARD		
CODE/PICTURES	DESCRIPTION	PRICE/DELIVERY
<b>FO-GRP64</b> 	<b>Forcar - Plasticized Grid mm 600x400</b>	<b>Delivery</b> from 4 to 9 days
<b>FO-GUT</b> 	<b>Forcar - Driving Couple</b>	<b>Delivery</b> from 4 to 9 days
<b>FO-GAR</b> 	<b>Forcar - Pair of anti-tilt guides</b>	<b>Delivery</b> from 4 to 9 days

