



**TECNOSERVICE'21 srl**

by Tinti Sergio  
Via Carlo Pisacane, 134  
61032 Fano (PU) Italy  
P.IVA IT0200411413

Tel. +39 0721 805911  
FAX +39 0721 809794  
e-mail: [staff@technochef.it](mailto:staff@technochef.it)  
[www.technochef.it](http://www.technochef.it)  
[www.technochef.eu](http://www.technochef.eu)

Services and Technologies for professional catering since 1973



CODE	DESCRIPTION	PRICE/DELIVERY
<b>FC-M-GN1410TN-FC</b>	2-door refrigerated cabinet, with monobloc, plug-in system, lt.1300, Temp. +0°/+8°C, ECOLOGICAL in Class D, Gas R290, Ventilated, Gastronorm 2/1, V.230/1, Kw . 0.508, weight 164 kg, dim.mm.1480x830x2010h.	<b>Delivery</b> from 8 to 15 days

#### PROFESSIONAL DESCRIPTION

**2 DOOR REFRIGERATED CABINET, with MONOBLOC, plug-in system, 1300 lt, ventilated, temp. +0°/ +8°C, ECOLOGICAL in Class D:**

- made of **AISI 201 stainless steel** ;
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement, quieter motor;
- **monobloc protected by stainless steel sheet** ;
- cabinet with **insulation thickness 60 mm** ;
- **chamber bottom with rounded corners** ;
- external bottom panels in galvanized sheet metal;
- **interior light** ;
- **door with return spring** ;
- door **locking** with **key** ;
- door seal removable without tools;
- gross capacity 1300 litres;
- suitable for containing **Gastronorm 2/1 grills or containers (650x530 mm)** ;
- operating temperature +0°/+8°C;
- electronic temperature control with digital thermostat;
- anti-corrosion treated evaporator;
- engine compartment with insulated sides;
- **ventilated refrigeration** ;
- **automatic defrost** ;
- **automatic evaporation of** condensation water;
- **ECOLOGICAL** Refrigerating Group with **R290 Gas** ;
- maximum ambient temperature: +38°C;
- maximum ambient humidity: 60% HR;
- Height-adjustable stainless steel feet.

**Supplied :**

- n.3 Gastro-Norm 2/1 grills;
- n.6 guides.

**CE mark**

**TECHNICAL CARD**

<b>power supply</b>	Monofase
<b>Volts</b>	V 230/1
<b>frequency (Hz)</b>	50
<b>motor power capacity (Kw)</b>	0,508
<b>net weight (Kg)</b>	164
<b>gross weight (Kg)</b>	189
<b>breadth (mm)</b>	1480
<b>depth (mm)</b>	830
<b>height (mm)</b>	2010

