



TECNOSERVICE'21 srl

by Tinti Sergio
Via Carlo Pisacane, 134
61032 Fano (PU) Italy
P.IVA IT0200411413

Tel. +39 0721 805911
FAX +39 0721 809794
e-mail: staff@technochef.it
www.technochef.it
www.technochef.eu

Services and Technologies for professional catering since 1973



| CODE | DESCRIPTION | PRICE/DELIVERY |
|--------------------------|--|-----------------------------------|
| FC-M-GN2100TN-FC | 2-door refrigerated table, with monobloc, plug-in system, capacity 282 litres, temperature -2°/+8°C, ventilated refrigeration, Gastronorm 1/1, ECOLOGICAL in Class C, Gas R600a, V.230/1, Kw.0,275, Weight 88 Kg, dim.mm.1360x700x850h | Delivery from 8 to 15 days |
| PROFESSIONAL DESCRIPTION | | |

REFRIGERATED TABLE 2 DOORS, with MONOBLOC, PLUG-IN SYSTEM, capacity 282 litres, temperature -2°C /+8°C, Gastronorm 1/1, ECOLOGICAL in Class D:

- **AISI 201 stainless steel structure,**
- **ventilated refrigeration ;**
- **compartments suitable for inserting Gastronorm 1/1 grills or trays (530x325 mm);**
- **the M line is characterized by: Monobloc refrigeration unit - refrigeration group with plug-in system** characterized by easy and immediate installation or possible removal/replacement;
- **monobloc in highly thermally insulating and completely recyclable plastic material ;**
- door with return spring;
- door seal removable without tools;
- bottom with rounded corners;
- easy interchangeability of doors with two and three drawer chests;
- easily extractable drawer units with telescopic stainless steel guides;
- **circular flow of the cold air so as not to directly touch the product ;**
- **electronic temperature control with digital thermostat ;**
- operating temperature -2°/+8°C;
- electric resistance around the door frame to eliminate condensation;
- **automatic defrost with electric resistance and automatic control of the defrost temperature ;**
- **automatic evaporation of condensation water ;**
- anti-corrosion treated evaporator;
- **height-adjustable stainless steel feet ;**
- possibility of leaning against the wall;
- easy interchangeability of doors with two and three drawer chests;
- **ECOLOGICAL Refrigerant Group with R600a gas;**
- **Energy Class D ;**
- insulation thickness 60 mm;
- max ambient temperature/humidity: +35°C / 55%HR;
- internal dimensions (mm): 900x530x560h;
- external dimensions (mm): 1360x700x850h.

Supplied :

- n.2 GN 1/1 grids (mm 530x325)
- n.4 guides.

Options/Accessories :


- pair of guides for GN 1/1 grill
- GN 1/1 plasticized grill
- kit of 4 wheels with a diameter of 120 mm, two of which with brakes
- Set of 2 drawers
- Set of 3 drawers

NOTE:

IT IS RECOMMENDED TO INSTALL ONLY THE CHEST OF DRAWERS WITH 2 DRAWERS IN THE COMPARTMENT NEAR THE REFRIGERATING UNIT , so as not to obstruct the circulation of the cold.

**CE MARK
MADE IN ASIA**

| TECHNICAL CARD | | |
|----------------|---------------------------|----------------|
| | power supply | Monofase |
| | Volts | V 230/1 |
| | frequency (Hz) | 50 |
| | motor power capacity (Kw) | 0,275 |
| | net weight (Kg) | 88 |
| | gross weight (Kg) | 106 |
| | breadth (mm) | 1360 |
| | depth (mm) | 700 |
| | height (mm) | 850 |
| TECHNICAL CARD | | |
| CODE/PICTURES | DESCRIPTION | PRICE/DELIVERY |

FOGRP11

GN 1/1 plasticized grid
Gastronorm 1/1 plasticized grid

Delivery from 4 to 9 days

FOCG11

Pair of guides for GN 1/1 grid support
Pair of guides for GN 1/1 grid support

Delivery from 4 to 9 days

FO-RUO120

Forcar - 4 wheels kit, 2 with brake
4 wheels kit with 120 mm diameter, 2 of which with brake.

Delivery from 4 to 9 days

FO-C12-FC

TECHNOCHEF - 2-drawer set, Mod.C12-FC
Set of 2 drawers

Delivery from 4 to 9 days

FO-C13-FC

TECHNOCHEF - 3-drawer set, Mod.C13-FC
Set of 3 drawers

Delivery from 4 to 9 days

